



TM200

Our Industrial ThinManager Ready® Thin Client features an ACP-enabled ThinManager® BIOS, providing an economical and highly reliable fanless virtualization solution.



logicsupply.com/tm200/



Low Profile Design

With its ultra-thin profile and solid state storage, the TM200 can be mounted where and how you need it.



Dependable Performance

Unlike other energy-efficient systems that struggle with processing-intensive tasks, the TM200 was built with versatility in mind and features powerful Intel processing.

Industrial Connectivity

Despite measuring less than 1.5" tall, the TM200 provides the industrial connectivity today's commercial applications demand.

US Office

Phone: +1 802 861 2300
Email: info@logicsupply.com
www.logicsupply.com

EU Office

Phone: +31 85 2733760
Email: info@logicsupply.eu
www.logicsupply.com

Specifications

| | | | |
|-----------------------------|---|------------------------------|---|
| Front I/O | 2 USB 2.0 ports Power button | Memory Type | DDR3L SO-DIMM (non-ECC) |
| Rear I/O | 2 USB 2.0 high current ports 2 USB 3.0 ports 2 RS-232 COM ports (Optional) 1 VGA port, 1 HDMI port for Dual Independent Display 1 Gb LAN port 2 Audio jacks 1 DC jack | Memory Capacity | Up to 8 GB |
| Processor | Intel Celeron J1900 | Memory Speed | 1333 MHz |
| Processor Speed | 2 GHz | LAN Controller | Realtek RT8111G-CG |
| Processor Generation | Bay Trail | Input Voltage | 8 ~ 19 V |
| Processor Cores | 4 | Power Input | DC jack |
| Graphics/GPU | Intel HD Graphics | Operating Temp. Range | 0°C ~ 55°C |
| | | Dimensions (WxHxD) | 196 x 37 x 213 mm |
| | | Case Material | Steel With Aluminum Extrusion |
| | | Mounting | DIN-mount, VESA MIS-D 100 mount, Wall-mount |

Dimensional Drawings

All measurements in mm

