



TM300

Rugged, fanless, and ideal for industrial virtualization, this system is ThinManager® Ready with an ACP-enabled BIOS.

logicsupply.com/tm300



Compact Footprint

Compact enclosure allows for easy installation in demanding environments.

Optimized Cooling

Fully fanless and ventless enclosure that protects it against dust, dirt, and vibration while keeping the system running cool.



Versatile Connectivity

Dual Gb LAN and dual independent display for increased reliability and productivity.

Specifications

Front I/O	2 USB 2.0 ports 2 RS-232/422/485 COM ports 1 CFAST slot 1 SIM card slot 1 expansion slot Power button Power mode switch
------------------	---

Rear I/O	1 USB 3.0 port 1 USB 2.0 port 1 DVI-I port 1 DisplayPort 2 Gb LAN ports 2 RS-232/422/485 COM ports 2 Audio jacks; line-out, mic-in 1 8-bit DIO port 1 secure DC input
-----------------	---

Processor	1.91 GHz Intel Atom E3845
------------------	---------------------------

Processor Socket	Onboard (BGA)
-------------------------	---------------

Processor Generation	Bay Trail
-----------------------------	-----------

Processor Cores	4
------------------------	---

Graphics/GPU	Intel HD Graphics
---------------------	-------------------

Memory Type	DDR3L SO-DIMM (non-ECC)
--------------------	-------------------------

Memory Capacity	4 GB
------------------------	------

Memory Speed	1333 MHz
---------------------	----------

Memory Slot	1
--------------------	---

Expansion Type	PCIe Mini Card (full-height) PCIe Mini Card (half-height)
-----------------------	--

Storage Options	1 x 2.5" HDD/SSD
------------------------	------------------

SATA Connectors	1 connector
------------------------	-------------

LAN Controller	Intel I210-AT Gb
-----------------------	------------------

Audio Controller	Realtek ALC888S codec
-------------------------	-----------------------

64-bit	Yes
---------------	-----

System Monitoring	Watchdog Timer
--------------------------	----------------

Input Voltage	9 ~ 48 V
----------------------	----------

Power Input	3-pin Terminal Block connector
--------------------	--------------------------------

Operating Temperature	-20°C ~ 70°C
------------------------------	--------------

Dimensions (mm)	185 x 131 x 54 mm 7.28" x 5.16" x 2.12"
------------------------	--

Case Type	Compact Fanless
------------------	-----------------

Case Material	Steel With Aluminum Extrusion
----------------------	-------------------------------

Port Punchouts	2x Antenna Holes
-----------------------	------------------

Mounting	Wall-mount, DIN
-----------------	-----------------

Included Accessories	Screws, AC Adapter
-----------------------------	--------------------

Certifications	CE, FCC, RoHS
-----------------------	---------------

Warranty	1 year warranty on parts and services
-----------------	---------------------------------------

Dimensional Drawings

All dimensions in mm

