


CA-132/132I Series

2-port RS-422/485 PC/104 modules with optional 2 kV isolation



- > 921.6 kbps maximum baudrate for super fast data transmission
- > On-chip software flow control
- > IRQ, I/O, and serial interface jumper and DIP switch selectable
- > Onboard Tx and Rx LED indicators for each port
- > Supports RS-485 ADDC® (Automatic Data Direction Control)
- > Windows CE 5.0/6.0 and Windows XP embedded operating systems supported
- > Wide temperature models available for -40 to 85°C environments

PCComm Lite



Overview

The CA-132/132I PC/104 modules are reliable, high performance, multiport serial communication solutions that have 2 RS-422/485 ports, and can be used with PC/104 CPU boards that accept the

PC/104 expansion interface. Optional DB9 and DB25 connection cables are available for connecting to serial devices, and the CA-132/132I's versatile driver support makes the modules suitable for a wide range of applications.

Specifications

Hardware

Comm. Controller: 16C550C or compatible x 2

Bus: PC/104 bus

Connector: 20-pin box header

LED Indicators: Built-in TX, RX LEDs for each port

DIP Switches: I/O base address, interrupt vector

Serial Interface

Number of Ports: 2

Serial Standards: RS-422/485

Max. No. of Boards per PC: 8

Serial Line Protection

Electrical Isolation: 2 kV (CA-132I only)

Performance

Baudrate: 50 bps to 921.6 kbps (supports non-standard baudrates)

Serial Communication Parameters

Data Bits: 5, 6, 7, 8

Stop Bits: 1, 1.5, 2

Parity: None, Even, Odd, Space, Mark

IRQ: 3, 4, 5, 6, 7, 9, 10, 11, 12, 15 (shared for all ports)

FIFO: 64 bytes

Serial Signals

RS-422: TxD+(B), TxD-(A), RxD+(B), RxD-(A), GND

RS-485-4w: TxD+(B), TxD-(A), RxD+(B), RxD-(A), GND

RS-485-2w: Data+(B), Data-(A), GND

Operating Systems

Windows: Windows 95/98/ME/NT, Windows 2000/XP/2003/Vista/2008/7/8/8.1/10 (x86/x64), Windows 2008 R2/2012/2012 R2/2016 (x64), DOS, Windows Embedded CE 5.0/6.0, Windows XP Embedded

Fixed TTY Drivers: QNX 4, QNX 6

Linux Real TTY Drivers: Linux 2.4.x, 2.6.x

Note: Please refer to Moxa's website for the latest driver support information.

Physical Characteristics

Dimensions: 90 x 96 mm (3.54 x 3.78 in)

Environmental Limits

Operating Temperature:

Standard Models: 0 to 55°C (32 to 131°F)

Wide Temp. Models: -40 to 85°C (-40 to 185°F)

Storage Temperature: -40 to 85°C (-40 to 185°F)

Ambient Relative Humidity: 5 to 95% (non-condensing)

Standards and Certifications

EMC: EN 55022/24, IEC 61000-6-2/6-4

EMI: FCC Part 15 Subpart B Class A

EMS:

IEC 61000-4-2 ESD: Contact 4kV; Air: 8kV

IEC 61000-4-3 RS: 80 MHz to 1 GHz: 3 V/m

IEC 61000-4-4 EFT: Power: 2 kV; Signal: 1 kV

IEC 61000-4-5 Surge: Power: 0.5 kV

IEC 61000-4-6 CS: 150 kHz to 80 MHz: 3 V/m; Signal: 3 V/m

IEC 61000-4-8 PFMF

Green Product: RoHS, CRoHS, WEEE

MTBF (mean time between failures)

Time: 536,288 hrs

Standard: Telcordia (Bellcore), GB

Power Requirements

Power Consumption:

CA-132: 155 mA @ +5 V

CA-132I: 190 mA @ +5 V

Warranty

Warranty Period: 5 years

Details: See www.moxa.com/warranty

: Ordering Information

Available Models

CA-132: 2-port RS-422/485 PC/104 module, 0 to 55°C operating temperature

CA-132I: 2-port RS-422/485 PC/104 module with electrical isolation, 0 to 55°C operating temperature

CA-132-T: 2-port RS-422/485 PC/104 module, -40 to 85°C operating temperature

CA-132I-T: 2-port RS-422/485 PC/104 module with electrical isolation, -40 to 85°C operating temperature

Package Checklist

- 1 CA-132 or CA-132I module
- Documentation and software CD
- Quick installation guide (printed)
- Warranty card