

CB-134I Series

4-port RS-422/485 PC/104-Plus modules with 2 kV isolation



- > 921.6 kbps maximum baudrate for super fast data transmission
- > On-chip S/W flow control
- > Serial interface is DIP switch selectable
- > Onboard Tx and Rx LED indicators for each port
- > Windows XP/Vista/7, Windows CE 5.0/6.0, and Windows XP embedded operating systems supported
- > Wide temperature model available for -40 to 85°C environments



Overview

The CB-134I PC/104-Plus modules come with 4 RS-422/485 ports, and can be used with PC/104-Plus CPU boards that accept the PC/104-Plus expansion interface. Optional DB9 and DB25 connection cables are available for connecting to serial devices, and the CB-134Is'

versatile driver support makes the modules suitable for a wide range of applications. The CB-134I modules can be used on the PC/104-Plus (PCI) bus, and provide a reliable, high performance solution for multiport serial communication.

Specifications

Hardware

Comm. Controller: MU860 (16C550C compatible)

Bus: PC/104-Plus bus

Connector: 40-pin box header

DIP Switches: Serial interface

Serial Interface

Number of Ports: 4

Serial Standards: RS-422/485

Max. No. of Boards per PC: 8

Serial Line Protection

Electrical Isolation: 2 kV

Performance

Baudrate: 50 bps to 921.6 kbps (supports non-standard baudrates)

Serial Communication Parameters

Data Bits: 5, 6, 7, 8

Stop Bits: 1, 1.5, 2

Parity: None, Even, Odd, Space, Mark

I/O Address: Assigned by BIOS

IRQ: Assigned by BIOS

FIFO: 128 bytes

Serial Signals

RS-422: TxD+(B), TxD-(A), RxD+(B), RxD-(A), GND

RS-485-4w: TxD+(B), TxD-(A), RxD+(B), RxD-(A), GND

RS-485-2w: Data+(B), Data-(A), GND

Operating Systems

Windows: Windows 95/98/ME/NT, Windows 2000/XP/2003/Vista/2008/7/8/8.1/10 (x86/x64), Windows 2008 R2/2012/2012 R2/2016 (x64), DOS, Windows Embedded CE 5.0/6.0, Windows XP Embedded

Fixed TTY Drivers: QNX 6

Linux Real TTY Drivers: Linux 2.4.x, 2.6.x

Note: Please refer to Moxa's website for the latest driver support information.

Physical Characteristics

Dimensions: 90 x 96 mm (3.54 x 3.78 in)

Environmental Limits

Operating Temperature:

Standard Models: 0 to 55°C (32 to 131°F)

Wide Temp. Models: -40 to 85°C (-40 to 185°F)

Storage Temperature: -40 to 85°C (-40 to 185°F)

Ambient Relative Humidity: 5 to 95% (non-condensing)

Standards and Certifications

EMC: EN 55022/24, IEC 61000-6-2/6-4

EMI: FCC Part 15 Subpart B Class A

EMS:

IEC 61000-4-2 ESD: Contact 4kV; Air: 8kV

IEC 61000-4-3 RS: 80 MHz to 1 GHz: 3 V/m

IEC 61000-4-4 EFT: Power: 2 kV; Signal: 1 kV

IEC 61000-4-5 Surge: Power: 0.5 kV

IEC 61000-4-6 CS: 150 kHz to 80 MHz: 3 V/m; Signal: 3 V/m

IEC 61000-4-8 PFMF

Green Product: RoHS, CRoHS, WEEE

MTBF (mean time between failures)

Time: 534,809 hrs

Standard: Telcordia (Bellcore), GB

Power Requirements

Power Consumption: 236 mA @ 5 VDC

Warranty

Warranty Period: 5 years

Details: See www.moxa.com/warranty

: Ordering Information

Available Models

CB-134I: 4-port RS-422/485 PC/104-Plus module with electrical isolation, 0 to 55°C operating temperature

CB-134I-T: 4-port RS-422/485 PC/104-Plus module with electrical isolation, -40 to 85°C operating temperature

Package Checklist

- 1 CB-134I or CB-134I-T module
- Documentation and software CD
- Quick installation guide (printed)
- Warranty card