

SPARTAN SERIES

*1.3 GHZ FIPS RADIO

FREEWAVE



KEY FEATURES

Max Speed: 115.2 kbps maximum throughput

Reliable: 100% tested for performance from -40°C to +75°C

Flexible: RS232 or Ethernet interfaces and user-programmable

Long Range: Up to 60 miles with clear line of sight

Powerful Diagnostics: Includes received signal strength indicator

Encryption: Certified by NIST for FIPS 140-2 Level 2

OVERVIEW

The Spartan M13 Series offered by FreeWave Technologies is designed to meet the rigorous demands of government and defense users worldwide. The 1.3 GHz products are available as OEM board level radios that are extremely user programmable including FIPS 140-2 Level 2 encryption. It is an affordable solution for UAV and UGV applications with serious size, weight and power constraints. The Spartan M13 Series shares the same features as other FreeWave radios that ensure reliable data transmission, such as 32 bit CRC error detection with automatic retransmission.

The FreeWave Spartan Series of wireless radios are designed to provide the performance, reliability and quality that our customers have come to know and expect in our products. The Spartan product family combines high performance with a small size making it ideal for applications where space is at a premium.

All radios are designed, manufactured and tested in Boulder, CO.

* This device is regulated under the U.S. International Traffic in Arms Regulation (ITAR). These regulations control the Export and Import of the defense articles. The device may only be sold or transferred to a non-U.S. party (in the U.S. or abroad) after authorization is obtained from the U.S. Department of State. Customer (a) agrees to comply with ITAR regulations and (b) shall be responsible for obtaining all necessary U.S. Government authorizations required to ensure compliance with these and other applicable U.S. Laws. Please contact FreeWave for export control information for specific products..

TECHNICAL SPECIFICATIONS

SPECIFICATIONS

M13-NCF	106.7 L x 50.8 W x 14.1 H (mm) Serial Board Level
M13-NCF-CC	106.7 L x 50.8 W x 14.1 H (mm) Conformal Coated M13-NCF
M13-NPF	103.9 L x 50.8 W x 18.1 H (mm) Ethernet Board Level

TRANSMITTER

Frequency Range	1.350-1.390 GHz
RF Data Rate	153 kbps or 115 kbps, user-selectable
Output Power	20 mW to 1 W
Data Link Range	60 miles, clear line of sight
Modulation	2 level GFSK
Occupied Bandwidth	230 kHz
Hopping Bands	7, user-selectable

RECEIVER

Normal Sensitivity	-103 dBm at 153 kbps, 1×10^{-6} BER -106 dBm at 115 kbps, 1×10^{-6} BER
Selectivity	20 dB at fc +/- 230 kHz

DATA TRANSMISSION

Error Detection	32 bit CRC, retransmit on error
Data Throughput	115.2 kbps and 80 kbps, user-selectable
Data Encryption	FIPS 140-2 Level 2
Protocol	M13-NCF: RS232 M13-NPF: IP
Data Interface	M13-NCF: 1.2 kbps to 115.2kbps M13-NPF: 10 Mbps/100 MBps
Connector	M13-NCF: Dual row, 14-pin, 2mm pin spacing, right-angle M13-NPF: Dual row, 10-pin male, 0.02 square posts, 2mm centers

POWER REQUIREMENTS

Operating Voltage	+4.75 VDC to +5.25 VDC	
+5 VDC Typical Current	Transmit: 1200 mA	Receive: 240 mA Idle: 135 mA

GENERAL INFORMATION

Operating Temperature	-40°C to +75°C
Humidity	0 to 95%, non-condensing
Dimensions	M13-NCF: 106.7 L x 50.8 W x 14.1 H (mm) M13-NPF: 103.9 L x 50.8 W x 18.1 H (mm)
Weight	M13-NCF: 66.6 g M13-NPF: 66.9 g
Antenna Connector	MMCX

APPLICATIONS



OIL & GAS



AGRICULTURE



UTILITIES



DEFENSE



SCADA



MINING



FLEET
MANAGEMENT



MUNICIPAL



ENTERPRISE

CONTACT US

5395 Pearl Parkway, Boulder, CO 80301
 TF 866.923.6168 T 303.381.9200
 For more information, visit www.freewave.com