

**B-Series**

**REMOTE PHOSPHOR HIGH BAY LIGHT**



\*B200 shown above

**FEATURES:**

- Instant strike
- -40°C to 45°C ambient temperature
- Glare free and uniform light distribution
- High CRI options
- Dimmable option, enabling the use of occupancy sensors for power savings
- Customizable and standard CCT options
- Up to 30% higher system efficacy compared to conventional LEDs
- Longer lifetime
- Universal AC input/full range, 90-305 VAC
- No mercury
- 5 year warranty
- Made in USA with global components

**OPERATING CHARACTERISTICS / ORDERING INFORMATION**

MODEL NUMBER	PRODUCT NUMBER	CRI	CCT	LUMENS *Estimate	TOTAL WATTS	LUMENS/WATTS	L90 HOURS
ETG-B100	RP750	70	5000K	10,146*	119	85.3	> 96,000
ETG-B200	RP750	70	5000K	20,918*	230	90.9	> 96,000

**POWER OPTIONS**

PRODUCT NUMBER	DESCRIPTION	B100	B200
P1	ON/OFF 90~305VAC	✓	✓
P4	Dimming 90~305VAC	✓	✓
P5	Transformer ON/OFF 480VAC	✓	✓
P6	Transformer Dimming 480VAC	✓	✓
P8	Dimming 24VDC	✓	✓