

LEDs

LED LINEAR RETROFITS



4' LED



8' LED

FEATURES:

- Shock and vibration resistant
- -20°C to 45°C ambient temperature
- No ballast required
- cUL listed
- No UV
- Moisture-proof, shatter-proof
- Instant strike, with full-light output
- Stable color
- Lifespan: 50,000+ hours
- No mercury
- 5 year warranty

OPERATING CHARACTERISTICS / ORDERING INFORMATION


PART NUMBER	LENGTH	CRI	CCT	LUMENS (*est)	LUMENS/WATTS	TOTAL WATTS	DLC
ETG-L04-40k-18W	4'	70	4000K	1,710	95	18	Yes
ETG-L04-50k-18W-DLC	4'	80	5000K	1,800	100	18	Yes
ETG-L04-60k-18W	4'	80	6000K	1,800	100	18	No
ETG-L08-60k-36W	8'	80	6000K	3,420	95	36	No

LED COMPONENT OPERATING SPECIFICATIONS

WATTAGE	VOLTAGE	CCT	LED QUANTITY	SIZE	COVER
18W	AC 100-277V	4000K - 5000K	290 pieces - 4ft.	1197*1mm - 4ft.	Frosted
36W			580 pieces - 8ft.	2368*1mm - 8ft.	

2D LIGHT INTENSITY DISTRIBUTION CURVE

Distance in units of Mounting Height; Values Based on 10ft Mounting Height; 1/2 Maximum Candela Trace Shown As Dashed Curve; (+) - Maximum Candela Point



SYSTEM WATTS

PROJECTED LIFESPAN

kWh USED OVER 50,000 HOURS

COST OF ELECTRICITY (@ 0.11/kWh)

TOTAL % ENERGY SAVINGS

SYSTEM WATTS

PROJECTED LIFESPAN

kWh USED OVER 50,000 HOURS

COST OF ELECTRICITY (@ 0.11/kWh)

TOTAL % ENERGY SAVINGS

18 WATT	REPLACES T12	
	40 WATT	32 WATT
18	44 w/ ballast	38 w/ ballast
50,000	9,000 - 30,000	9,000 - 30,000
9,000 kWh	2,200 kWh	1,900 kWh
\$99.00	\$242.00	\$209.00

59%

53%

36 WATT	REPLACES T12	
	75 WATT	60 WATT
36	81 w/ ballast	66 w/ ballast
50,000	12,000	12,000
1,800 kWh	4,050 kWh	3,300 kWh
\$198.00	\$445.50	\$363.00

56%

45%