

Wireless Manual Zoom, Outdoor HD IP Camera

MZ-HD32-3

- 1080p HD resolution
- Day/night switching for almost any lighting condition
- H.264, MJPEG
- Suitable for harsh weather conditions



Rugged high-definition video camera for low light conditions

The MZ-HD32-3 is a high-quality, high resolution wireless color video camera with a vari-focal lens and auto-iris. It will produce high-definition video in low light conditions. This high-resolution, HD camera supports 1080p resolution at 30 frames per second in multiple codecs, including MJPEG and H.264 video. The standard lens is adjustable from 2.8 to 12.0 mm, to provide a horizontal field-of-view of 86 degrees.

The camera can accept one contact closure or TTL input

from an auxiliary security or process monitoring device to initiate automatic views and video recordings of intrusions or process malfunctions.

The camera is housed in an IP65, NEMA 4 rated weatherproof enclosure with an automatic heater and blower. It comes ready for mounting and requires only power. IVC also offers a variety of wireless access points to complete your wireless network.

► specifications

Imager	1/2.7" Progressive Scan CMOS
Shutter	1 to 1/10,000 seconds
Minimum Illumination	0.2 Lux (Color) to 0.03 Lux (B/W)
White Balance	Auto and Manual
Iris	Auto
Focus	Auto and Manual
View Angle	48° - 86°
Focal Length	2.8 - 12 mm
F-number	1.2
Ethernet	Wireless (See Ordering Information)
Resolution	1920 x 1080
I/O Terminals	1 Input, 1 Output
Compression	M-JPEG, H.264
Frame Rate	25 FPS (PAL), 30 FPS (NTSC)
Protocols	TCP/IP, HTTP, FTP, SMTP
Weight	10 lbs.
Voltage Required	110 VAC
Power Consumption	23.5 W
Operating Temperature	-29° to 50° C
Dimensions	18" L x 5" D (without sunshield)
Rating	IP65, NEMA 4

► IVC camera management software

Point & click camera management & control

Robust, enterprise class software to manage and control your cameras and video from anywhere in the world.



► features



1080p high-definition broadcast quality images for detailed post-event analysis



Wireless connectivity



Day/night switching provides for black and white video under very dark conditions



Rated IP65, NEMA 4

► accessories

MB-100 Pole mount bracket

► ordering information

MZ-HD32-3-XX-V

-V	Voltage Required
110	110-120 VAC
230	220-240 VAC
24D	24 VDC

IP Connection Options	
-XX	Radio
AGN	IEEE 802.11a/n or IEEE 802.11b/g/n



MADE IN THE USA

330 Nevada St., Newton, MA 02460 www.ivcco.com 617-467-3059

© 2015, Industrial Video & Control Co. The Industrial Video & Control Co. logo is a registered trademark of Industrial Video & Control Co.. All other company names and products are trademarks or registered trademarks of their respective companies. All information provided is subject to change without notice. 9/23/2015

IVC
&
INDUSTRIAL VIDEO & CONTROL