

Pan/Tilt/Zoom HD Color Camera

PTZ-HD30-01

- 1080p HD video with 20x optical zoom
- Suitable for harsh weather environments & indoor applications
- H.264, MJPEG multi-streaming
- Day/night switching



Rugged 1080p HD camera for indoor/outdoor applications

The PTZ-HD30-01 is a high quality, high-definition color video camera with outstanding low-light performance. It has a 20x motor-driven optical zoom. The PTZ-HD30-01 can provide multiple streams of high frame rate video. The camera automatically switches to black and white and removes an IR cut filter to increase sensitivity in low light conditions.

The high speed pan, tilt, and zoom functions can be controlled automatically and precisely from anywhere using the click-to-point and preset view features of IVC's camera management software packages.

The camera is housed in a weatherproof enclosure rated IP66. It requires only a power source and Ethernet connection for installation.

► specifications

| | |
|-----------------------|---------------------------------|
| Imager | 1/2.8" Progressive Scan CMOS |
| Resolution | 1920 x 1080 |
| Shutter Speed | 1 to 1/10,000 Seconds |
| Minimum Illumination | 0.05 Lux (Color) 0.01 Lux (B/W) |
| F number | F1.6 |
| Focal Length | 4.7 – 94 mm |
| Zoom ratio | 20x |
| Iris | Auto and Manual |
| Day/night | Auto |
| Focus | Auto and Manual |
| White Balance | Auto, Manual, ATW |
| Pan Angle | 360° |
| Pan Speed | 400° Per Second |
| Tilt Angle | -10° to 190° |
| Tilt Speed | 400° Per Second |
| I/O Terminals | 4 Inputs; 2 Outputs |
| Ethernet | 100Base-TX/10BaseT (RJ-45) |
| Protocols | TCP/IP, HTTP, HTTPS, FTP, SMTP |
| Compression | M-JPEG, H.264 |
| Frame Rate | 30 FPS |
| Voltage Required | 24 VAC, PoE* |
| Power Consumption | 60W maximum (with heaters on) |
| Weight | 5.11 lbs. |
| Operating Temperature | -40° C to 60° C |
| Dimensions | 11.1" H x 7.55" W x 7.55" D |
| Mount | Wall mount standard |
| Enclosure Rating | IP66 |

* PoE version includes compatible PoE injector

► accessories

| | |
|---------------------|------------------------------|
| RSC-4050-32m | 32 GB microSDHC Storage Card |
| RSC-4050-64m | 64 GB microSDHC Storage Card |
| MB-100 | Pole Mount Bracket |
| MB-127-01 | Ceiling Mount Bracket |

► ordering information

PTZ-HD30-01-C-Fn-V

| | |
|------|----------------------|
| -V | Voltage Required |
| 24 | 24 VAC |
| POEt | Power over Ethernet* |
| -Fn | Connection Type |
| 1 | 10/100 RJ-45 |
| -C | Camera |
| 20 | 20x Optical Zoom |

► IVC camera management software

Point & click camera management & control

Robust, enterprise class software to manage and control your cameras and video from anywhere in the world.



MADE IN THE USA

330 Nevada St., Newton, MA 02460 www.ivcco.com 617-467-3059

© 2015, Industrial Video & Control Co. The Industrial Video & Control Co. logo is a registered trademark of Industrial Video & Control Co.. All other company names and products are trademarks or registered trademarks of their respective companies. All information provided is subject to change without notice. 9/23/2015

IVC
&
INDUSTRIAL VIDEO & CONTROL