



21.5" Compact Open HMI



- 1920 x 1080 Pixel High-Resolution TFT
- Intel Celeron N2930 1.83 GHz Quad-Core Processor
- Onboard DDR3L 4 GB 1600 MHz
- 2 Ethernet Ports, 2 Serial Ports, 2 USB Ports

System	CPU	Intel Celeron N2930 1.83 GHz Quad-Core processor
	System Chipset	SoC
	System Memory	Onboard DDR3L 4 GB 1600 MHz
I/O Ports	USB	2 x USB 3.0 type A
	Serial	COM1: RS-232/422/485 DE-9P (default RS-232) COM2: RS-232 DE-9P
	Audio	1 x 3.5 mm line out
	LAN	GbE RJ-45 x 2
	Power	3-pin connector header, DC power input
	Remote Power Switch	2-pin connector header
	Storage	Solid State Drive
SD Card Slot		1 x internal secure digital memory card socket, up to 32 GB
Expansion	Expansion Slot	N/A
Display	Display Type	21.5" TFT-LCD
	Max. Resolution	1920 x 1080
	Max. Color	16.7 M
	Luminance (cd/m ²)	250
	View Angle (H°/V°)	178/178
	Contrast Ratio	3000:1
	Backlight Lifetime (hours)	30,000+
Touch Screen	Type	5-wire resistive touch
	Interface	USB
	Light Transmission	80%
Electrical	Input Voltage	9~36 VDC
	Input Current	0.7 ~ 3.0 A
	Input Power	26.7 W
Mechanical	Construction	Silver aluminum front bezel and chassis
	Rating	IP65 front panel / NEMA4X
	Mounting	Panel mounting, VESA 100 x 100
	Dimension (W x H x D)	21.93 x 14.25 x 2.55 inches [557 x 362 x 64.8 mm]
	Net Weight	17.20 lbs [7.8 kg]
Environmental	Operating Temperature	32~122°F [0~50°C]
	Storage Temperature	-4~140°F [-20~60°C]
	Storage Humidity	10 to 90% @ 40°C, non-condensing
	Certification	CE / FCC Class A / cULus / RoHS
Operating System	Type	Base Model: Microsoft Windows® Embedded Standard 7 32-bit or 64-bit (WS7P)* Upgrade Option: Microsoft Windows® 7 Pro for Embedded 32-bit or 64-bit (FES 7 Pro)*
Notes	Specifications subject to change without notice. * 32-bit or 64-bit must be specified at the time the order is placed.	