

Smart-Device Compatible HMI with Built-In OPC UA



- 32-bit RISC Cortex-A8, 600 MHz CPU
- 256 MB Flash, 256 MB RAM Memory
- 2 Ethernet, 1 Serial Port, 1 USB Port
- Works with Apple/Android Tablets and Smart Phones
- Displayless HMI using EZware Plus

System	CPU	32-bit RISC Cortex-A8, 600 MHz
	Memory (RAM)	256 MB
	Memory (Flash)	256 MB
	RTC	Built-in
I/O Ports	Serial Ports	1 x DE9P COM1: RS-232, COM2: RS-485 2 or 4 wire, COM3: RS-485 2 wire N/A
	Ethernet	2 x 10/100/1000 Base-T
	CANbus	N/A
	USB Host	1 x USB 2.0
	USB Client	N/A
	Audio	N/A
	Video	N/A
	Wi-Fi	N/A
	HDMI	N/A
	SD Card Slot	SD/SDHC
Display	Display Type	N/A
	Size (W x H)	N/A
	Resolution (pixels)	N/A
	Luminance (cd/m ²)	N/A
	Contrast Ratio	N/A
	Max. Colors	N/A
	LED Backlight Longevity Hrs.	N/A
Touch Screen	Type	N/A
	Active Area Accuracy	N/A
Electrical	Input Voltage	24 ± 20% VDC
	Input Current	230 mA @ 24 VDC
	Power Isolation	Built-in
	Isolation Resistance	Exceed 50 MΩ at 500 VDC
Mechanical	Enclosure	Plastic, charcoal grey
	PCB Coating	Yes
	Dimensions (W x H x D)	5.12 x 4.53 x 1.06 inches [130 x 115 x 27 mm]
	Weight	0.40 lbs. [0.18 kg]
Environmental	Mounting	35 mm DIN rail mounting
	Operating Temperature	-4° ~ 131°F (-20° ~ 55°C)
	Storage Temperature	-4° ~ 158°F (-20° ~ 70°C)
	Relative Humidity	10% ~ 90% (non-condensing)
	Vibration Endurance	10 to 25 Hz (X, Y, Z direction, 2G, 30 minutes)
	Rating	IP20
Software	Certifications	cULus, CE, RoHS
	Software	EZwarePlus (v5.05.02.114 or later) OPC UA License comes pre-installed on unit
Notes		