



## 4 x 20 VFD Display



- 4 Line by 20 Character VFD Display
- Membrane Keypad with Customizable Key Legend Insert
- 24 Programmable Keys
- 1 Serial RS232/422/485 Port

<b>System</b>	Capacity (screens)	500
	Audio	Internal audio transducer
<b>I/O Ports</b>	Serial	1 x RJ45 shielded RS-232/422/485
	Power	3 pins terminal block connector, DC power input
<b>Display</b>	Type	VFD; 5 x 7 dot matrix
	Size	4 line by 20 characters
	Viewing Angle (°)	Approximately 90 degree
<b>Keypad</b>	Type	Flat panel membrane
	Material	Polyester
	Lifespan	3 million operations
	Programmable Keys	24 (up to 8 screen-dependent)
	Customizable Key Legend	Yes
<b>Electrical</b>	Input Voltage	12 ~ 30 VDC
	Input Power	2.02 W
	Input Current	84 mA @ 24 VDC
<b>Mechanical</b>	Enclosure	Aluminum
	Dimensions (W x H x D)	6 x 5 x 1.77 inches [152.4 x 127 x 45 mm]
	Panel Cutout Dim. (W x H)	N/A
	Weight	0.85 lbs [0.38 kg]
<b>Environmental</b>	Mounting	Panel mounting
	Operating Temperature	14 ~ 149°F (-10 ~ 65°C)
	Storage Temperature	-22 ~ 176°F (-30 ~ 80°C)
	Relative Humidity	5% ~ 95% (non-condensing)
	Rating	NEMA4X / IP65
<b>Notes</b>	Certifications	CE / cULus (Class I, Division 2)
	Specifications subject to change without notice. For panel cutout dimensions, please refer to dimensional drawing.	