


Transformer Specifications	
PRIMARY VOLTAGE(S)	120x240
SECONDARY VOLTAGE(S)	24
RATED V.A.	750
RATED FREQUENCY	50/60
INSULATION CLASS	130
AGENCY APPROVALS	UL, CUL
ESTIMATED WEIGHT	27.0 LBS

TEST REQUIREMENTS			
WINDING	H4-H3	H2-H1	X2-X1
D.C. VOLTS	120	120	25.3
LOAD VOLTS	120	120	24
F.L. AMPS	3.556	3.556	31.25
HI-POT	4800V		
EXCITING AMPS	1.25AMPS @ 120 VOLTS, 50HZ		
EXCITING WATTS	330		



NOTE:
 1. FUSE CLIPS TO ACCOMMODATE 13/32-1 1/2"
 2. ALL MEASUREMENTS IN INCHES (MM)

MAIN PRODUCT IDENTIFICATION LABEL

MICRON
 CONTROL PRODUCTS
 8101 OGDEN AVENUE
 WILMINGTON, OHIO 46093
 WWW.MICRONTRANSFORMERS.COM

ImperVITRAN
 U.S. PAT. NO. 3516041

750VA 50/60HZ
 TEMP CL. 130°C

UL US
 CAT B750LP7JKF
 SERIES 2

Listed 702X 04083

REVISIONS	BY	DATE
A	NEW	1/17/08

PACKAGED ACCESSORIES	
1	PAIR OF JUMPERS

DATE: 1/17/08
 RELEASE DATE: 1/17/08
 MICRON PART NO. B750LP7JKFA9999A2
 B750LP7JKFA7777B2
 B750LP7JKF