

Software Name: Software Package for EDS-P510 Series (MXview Trial)

Version No.	Build Date No./ Release Date	Supported OS	Apply to Models	New Features/ Enhancements	Bugs Fixed/Changes	Note
v2.9	N/A	Windows_7, Windows_8, Windows_10, Windows_Server_2008, Windows_Server_2012	N/A	<p>New Features:</p> <ol style="list-style-type: none"> 1. Customized name for port label 2. Inventory report can export to PDF or CSV file 3. Support the PRP/HSR topology on PT-7728-PTP 4. The old version database can be upgrade to the current version and restore. 5. Following model supported: <ol style="list-style-type: none"> a. MGate 5103 b. MGate 5111 c. AWK-1137C d. TAP-213 e. PT-G7728/G7828 f. EDS-P506E 6. Security view supported in the following model: <ol style="list-style-type: none"> a. EDR-G902/G903 (with firmware after v4.2) c. EDR-810 (with firmware after v4.2) d. MGate-5118, e.MGate 5101-PBM-MN, f. MGate 5103 g. MGate 5109 h. MGate W5108 i. MGate W5208 <p>Enhancements:</p> <ol style="list-style-type: none"> 1. Icon, topology, background image and the document of device is remained after upgrade the MXview 2. Prevent nonprivileged local user to execute arbitrary code with elevated privileged on the system. 3. HTTPS certs will not show under web folder. 4. RSA keys of SSL certificate increase from 1024 to 2048 bits 	<p>Bugs Fixed:</p> <ol style="list-style-type: none"> 1. ICMP and SNMP pooling interval value don't change after restart the MXview 2. Unexpected large packet could potentially crash MXview Server 3. Remote user can read the random generated private key for MXview's self-signed certification. 4. PT-7528 hardware version 2.0 can't be viewed 5. Set SNMPv3 auth type at add device, only SHA will be activated event choose MD5 or SHA <p>Changes:</p> <ol style="list-style-type: none"> 1. modify the scenario of virtual demo 	N/A