

Software Name: Firmware for NPort IA5150A/IA5250A Series

Version No.	Build Date No./ Release Date	Supported OS	Apply to Models	New Features/ Enhancements	Bugs Fixed/Changes	Note
v1.3	Build 16100514	N/A	NPort IA5150A, NPort IA5150AI, NPort IA5150AI-T, NPort IA5150A-T, NPort IA5250A, NPort IA5250AI, NPort IA5250AI-T, NPort IA5250A-T, NPort IA5150A-IEX, NPort IA5150AI-IEX, NPort IA5150AI-T-IEX, NPort IA5150A-T-IEX, NPort IA5250A-IEX, NPort IA5250AI-IEX, NPort IA5250AI-T-IEX, NPort IA5250A-T-IEX	<p>New Features: N/A</p> <p>Enhancements:</p> <ol style="list-style-type: none"> Enhanced web login security and supports 5 users logged in simultaneously. Extended HTTP challenge ID length from 32 bits to 256 bits. Enabled the default password "moxa". Increased CSRF protection mechanism. Increased XSS protection mechanism. The IP address of the NPort can be set to an address ending with 0 or 255. Supports "ARP probe" in RFC5227. NPort would respond for ARP requests with sender IP address 0.0.0.0. 	<p>Bugs Fixed:</p> <ol style="list-style-type: none"> NPort cannot send email using Google's SMTP server. In pair connection mode, master does not pull down RTS/DTR signal after the TCP connection is broken. Command port sends lots of "D_ASPP_CMD_ALIVE" packets after running for 50 days. NPort may reboot or hang from several buffer overflow attacks through Telnet, SSH, DSCI, SNMP, HTTP, and HTTPS. <p>Changes: N/A</p>	N/A

Software Name: Firmware for NPort IA5150A/IA5250A Series

Version No.	Build Date No./ Release Date	Supported OS	Apply to Models	New Features/ Enhancements	Bugs Fixed/Changes	Note
v1.2	Build 15041515	N/A	NPort IA5150A, NPort IA5150AI, NPort IA5150AI-T, NPort IA5150A-T, NPort IA5250A, NPort IA5250AI, NPort IA5250AI-T, NPort IA5250A-T, NPort IA5150A-IEX, NPort IA5150AI-IEX, NPort IA5150AI-T-IEX, NPort IA5150A-T-IEX, NPort IA5250A-IEX, NPort IA5250AI-IEX, NPort IA5250AI-T-IEX, NPort IA5250A-T-IEX	<p>New Features: N/A</p> <p>Enhancements:</p> <ol style="list-style-type: none"> 1. Uses model name instead of "NULL" for SNMP object "sysDescr". 2. Supports connecting to the server by domain name and the server IP will change dynamically. 3. Supports updating the ARP table by gratuitous ARP. 4. Supports time synchronization with an NTPv4 server. 5. Supports RFC2217 NOTIFY-LINESTATE for Transfer Shift Register Empty and Transfer Holding Register Empty. 	<p>Bugs Fixed:</p> <ol style="list-style-type: none"> 1. If an SNMP GETNEXT command is issued on an object that does not exist, 'no such name error' is displayed. 2. When DHCP renews IPs, if the IP was originally given by a relay agent, NPort should send a DHCP request to the relay agent, not the DHCP server. 3. In Real COM mode, when the modem status of the NPort's serial port is changed frequently, the NPort will sometimes fail to notify the change to the driver. 4. In reverse telnet mode, the NPort will try to subnegotiate the COM port control options without option negotiation first. 5. In RFC2217 Mode, if the Ethernet data has many FF characters, some data may be lost while passing the data to the serial side. 6. Modified parsing data mechanism to fix import file failure. 7. Unable to see the baud rate through a Telnet console on the "View settings" side. 8. System reboots when receiving IGMP packets. 9. The trap settings for port auto warning in the configuration file will be set to email settings after import. 10. When both serial ports are set to TCP server mode, the connection on port 1 works normally, but will fail after a connection on port 2 is established. <p>Changes: N/A</p>	N/A