

Software Name: IExpress Configuration Utility

Version No.	Build Date No./ Release Date	Supported OS	Apply to Models	New Features/ Enhancements	Bugs Fixed/Changes	Note
v2.3.0	Build18111510	Windows_Server_2008_R2, Windows_Server_2012_R2	ioLogik 2500 Series, ioThinX 4510 (-T)	New Features: <ol style="list-style-type: none"> 1. Supports mass deployment of ioThinX 4510 devices. 2. Configuration update. 3. Configuration export. 4. Firmware update. 5. Device time setting. 6. Device restart. 7. Loading the factory default setting. Enhancements: N/A	Bugs Fixed: <ol style="list-style-type: none"> 1. The deployment UI does not refresh after the search function has run. Changes: <ol style="list-style-type: none"> 1. IP address will be updated after the configuration is imported. 	N/A
v2.1.0	Build18012318	Windows_10, Windows_7, Windows_8, Windows_Server_2003, Windows_Server_2008, Windows_Server_2008_R2, Windows_Server_2012, Windows_Server_2012_R2	ioLogik 2512, ioLogik 2512-T, ioLogik 2542, ioLogik 2542-T, ioLogik 2512-GPRS, ioLogik 2512-GPRS-T, ioLogik 2542-GPRS, ioLogik 2542-GPRS-T, ioLogik 2512-HSPA, ioLogik 2512-HSPA-T, ioLogik 2542-HSPA, ioLogik 2542-HSPA-T, ioLogik 2512-WL1-EU, ioLogik 2512-WL1-EU-T, ioLogik 2512-WL1-US, ioLogik 2512-WL1-US-T, ioLogik 2512-WL1-JP, ioLogik 2512-WL1-JP-T, ioLogik 2542-WL1-EU, ioLogik 2542-WL1-EU-T, ioLogik 2542-WL1-US, ioLogik 2542-WL1-US-T, ioLogik 2542-WL1-JP, ioLogik 2542-WL1-JP-T	New Features: <ol style="list-style-type: none"> 1. Supports multiple threads for mass deployment. 2. Quick launch bar added. 3. Supports configuration duplicates with serial number IP & server name. Enhancements: <ol style="list-style-type: none"> 1. Enhanced UI wording and user flow. 2. Quick launch icons added. 3. Search Remind Settings added. 4. Enhanced Search Device panel for searching in LAN, WAN, and in CDA. 5. Display channel alias name in Click&Go Plus Keyword Lookup. 	Bugs Fixed: <ol style="list-style-type: none"> 1. Changed TCP Message Wording UNICODE to UTF-8. 2. Fixed Daylight Saving User Interface Issue. 3. Fixed recipient cannot receive SMS after the phone number is changed in the Phone Book. 4. Removed WL1 802.11a option. 5. Fixed failure when configuring Click&Go FTP setting after deleting the first Data Logging profile. 6. Fixed wrong query message of GET method in Click&Go CGI Command (As Client) after saving to a configuration file. 7. Fixed failure when executing Click&Go simulator if configuring comparison between AI and IR values in IF condition. Changes: <ol style="list-style-type: none"> 1. Changed Data buffer for network failure Parameter from AOPC Server Connection to Data Logging (Required memory: 2 GB). 	N/A

Software Name: IExpress Configuration Utility

Version No.	Build Date No./ Release Date	Supported OS	Apply to Models	New Features/ Enhancements	Bugs Fixed/Changes	Note
v2.0.0	Build16071913	Windows_10, Windows_7, Windows_8, Windows_Server_2003, Windows_Server_2008, Windows_Server_2008_R2, Windows_Server_2012, Windows_Server_2012_R2	ioLogik 2512, ioLogik 2512-T, ioLogik 2542, ioLogik 2542-T, ioLogik 2512-GPRS, ioLogik 2512-GPRS-T, ioLogik 2542-GPRS, ioLogik 2542-GPRS-T, ioLogik 2512-HSPA, ioLogik 2512-HSPA-T, ioLogik 2542-HSPA, ioLogik 2542-HSPA-T, ioLogik 2512-WL1-EU, ioLogik 2512-WL1-EU-T, ioLogik 2512-WL1-US, ioLogik 2512-WL1-US-T, ioLogik 2512-WL1-JP, ioLogik 2512-WL1-JP-T, ioLogik 2542-WL1-EU, ioLogik 2542-WL1-EU-T, ioLogik 2542-WL1-US, ioLogik 2542-WL1-US-T, ioLogik 2542-WL1-JP, ioLogik 2542-WL1-JP-T	New Features: <ol style="list-style-type: none"> Added data buffer setting for data supplement function of MX-AOPC UA Logger. Added User Settings for three roles, Administrator, Operator, and User. Added Access Control for allowing IP address to access with Modbus protocol. Added three TC modes (78.126 mV, 39.062 mA, and 19.532 mV) of ioLogik E1262 as I/O expansion. Added "Power on Delay" settings for relay channels of ioLogik E1214 as I/O expansion. Added Modbus address for raw value of AI, AO, TC, and RTD. Added Modbus address for relay current count value, relay total count value, and reset relay current count value of ioLogik E1214 as I/O expansion. Added IF condition of Click&Go Plus for "relay current count value" and "total count value". Added Action of Click&Go Plus for "Reset relay current count value". Added Modbus host connection timeout settings. Added IF condition of Click&Go Plus for "Modbus host connection status" . Added IF condition of Click&Go Plus for RTD and TC value comparison. Added enable/disable FTP server service option . Added timestamp options (device 	Bugs Fixed: <ol style="list-style-type: none"> Removed "Server_Location" from lookup table. Fixed AI scaling unit column was covered. Changes: N/A	N/A

Software Name: IOxpress Configuration Utility

Version No.	Build Date No./ Release Date	Supported OS	Apply to Models	New Features/ Enhancements	Bugs Fixed/Changes	Note
				<p>local time or UTC and time zone) for data logging function.</p> <p>15. Added Peer-to-Peer disconnection mode settings for DO and AO channels.</p> <p>16. Added communication timeout settings for FTP Client, Email, CGI Command Client, TCP Message, and Remote Action Client.</p> <p>17. Added checksum algorithm to improve correctness of configuration file transfer between IOxpress and Device.</p> <p>18. Added search device by IP address.</p> <p>19. Added IF condition of Click&Go Plus for "Cellular link up".</p> <p>20. Added RSSI tag.</p> <p>21. Added "Cellular IP" in keyword lookup options of SNMP trap, TCP/UDP message, email, and SMS.</p> <p>22. Changed delete icon position of Click&Go Plus.</p> <p>23. Added warning message before deleting the Click&Go Plus rule.</p> <p>24. Added "Restore Default" button for Modbus function.</p> <p>25. Improved cellular reconnection user interface.</p> <p>26. Removed "Modify User Name & Password" function from Mass Deployment.</p> <p>Enhancements: N/A</p>		

Software Name: IExpress Configuration Utility

Version No.	Build Date No./ Release Date	Supported OS	Apply to Models	New Features/ Enhancements	Bugs Fixed/Changes	Note
v1.3.0	Build15092616	Windows_10, Windows_7, Windows_8, Windows_Server_2003, Windows_Server_2008, Windows_Server_2008_R2, Windows_Server_2012, Windows_Server_2012_R2	ioLogik 2512, ioLogik 2512-T, ioLogik 2542, ioLogik 2542-T, ioLogik 2512-GPRS, ioLogik 2512-GPRS-T, ioLogik 2542-GPRS, ioLogik 2542-GPRS-T, ioLogik 2512-HSPA, ioLogik 2512-HSPA-T, ioLogik 2542-HSPA, ioLogik 2542-HSPA-T, ioLogik 2512-WL1-EU, ioLogik 2512-WL1-EU-T, ioLogik 2512-WL1-US, ioLogik 2512-WL1-US-T, ioLogik 2512-WL1-JP, ioLogik 2512-WL1-JP-T, ioLogik 2542-WL1-EU, ioLogik 2542-WL1-EU-T, ioLogik 2542-WL1-US, ioLogik 2542-WL1-US-T, ioLogik 2542-WL1-JP, ioLogik 2542-WL1-JP-T	New Features: 1. Support ioLogik 2500-WL1. Enhancements: N/A	Bugs Fixed: N/A Changes: N/A	N/A