Nematron® ePC070WMT

(intel)

7.0" Widescreen, Low-Cost, Fanless, Panel Mount Industrial Computer

ePC070WMT Overview

The Nematron ePC070WMT is a high performance, fanless, panel mount computer specifically designed to be installed as an automation control interface. The ePC070WMT is widely used in many vertical manufacturing industries and by industrial OEMs.

Why Nematron?

- Internationally certified
- Unprecedented uptime
- Best in class lead times to meet your schedules and deadlines
- Long product lifecycles that help reduce your cost of ownership

Target Industries

- Automotive
- Food & beverage
- Packaging
- Power generation

Rugged, Superior Quality

- All aluminum construction
- Widescreen, multi-touch
- Solid state drives no moving parts
- Intel® high performance processor

Safety-Tested Reliability

- UL/cUL 60950 approved
- CE approved
- Temperature and humidity tested to 50°C
- IP65 front panel
- 2-year warranty



















Nematron® ePC070WMT

PHYSICAL SPECIFICATIONS		
Dimensions (inch/mm)	7.95"W x 5.86"H x 1.53"D	
	202mm x 149mm x 39mm	
Cutout (inch/mm)	7.55" x 5.43" / 192mm x 138mm	
Weight	2.6 lbs. (1.2kg)	
DISPLAY SPECIFIC	ATIONS	
LCD Size	7.0"	
Resolution	880 x 480 Widescreen	
Display Colors	262K	
Brightness	350 cd/m² (NIT) Standard	
Viewing Angle	±140° Horizontal / ±110° Vertical	
Touchscreen	Projected Capacitive Multi-Touch	
Contrast ratio	400:1 (Typical)	
Backlight Life	40,000 Hours	
PROCESSOR		
Type & Processor	Intel® Quad Core Celeron N2930	
Core Speed	Up to 2.16 GHz	
L2 Cache	2MB	
Chipset	Intel Bay Trail-M	
POWER		
DC Input Power	9-36 VDC, 4.5A-1.5A	
	(Must be Powered by a Listed ITE LPS Power Source)	

External AC-to-DC Adapter (Universal AC Input)

STORAGE & PERIPHERALS		
Operating System	Windows® 7 Professional (32-bit); Windows 7 Ultimate (64-bit), Windows 10 IoT Enterprise (32-bit or 64-bit) (optional)	
DRAM	4GB (On-board DDR3L 1333MHz Dual Channel)	
Standard Storage	128GB Solid State Drive; 256GB Solid State Drive (optional)	
Available I/O	(1) HDMI Port, (1) USB 2.0, (1) USB 3.0, (1) RS-232, (1) RS-232/422/485, (2) Gigabit Ethernet 10/100/1000, (1) Audio Out	
ENCLOSURE		
Material	Die Cast Aluminum Enclosure, IP65 Compliant Aluminum Front Panel (when installed in an appropriate enclosure)	
Mounting	Panel, VESA 75 x 75	
COMPLIANCE		
Compliance	CE, FCC Class A	
Safety Agency	UL/cUL 60950 (ordinary locations) Indoor Use only	
ENVIRONMENTAL		
Operating Temperature	-0°C ~ 50°C	
Storage Temperature	-20°C ~ 60°C	
Humidity	10%~90% (Non-Condensing)	

PART NUMBER CONFIGURATOR

ePC070WMT-N2930-4GB-128SS-W7

Display Size: ——	
070WMT	7.0" Widescreen Multi-Touch
Processor: -N2930	Intel Celeron N2930 Processor (Fanless)
DRAM:	
-4GB	4GB DRAM
Internal Storage	•
-128SS	128 GB internal Solid State Drive
-256SS	256 GB internal Solid State Drive
Operating Syste	mar.

Operating System:

AC Power Supply

-W7 Windows 7 Professional (32-bit) -W7U Windows 7 Ultimate (64-bit)

-W1032 Windows 10 IoT Enterprise (32-bit) ¹ -W1064 Windows 10 IoT Enterprise (64-bit) 1



¹ Windows 10 IoT Enterprise is the OEM equivalent to Windows 10 Professional.