Nematron[®] ePC101WMT

10.1" Widescreen Low-Cost, Fanless, Panel Mount Industrial Computer

ePC101WMT Overview

The Nematron ePC101WMT is a high performance, fanless, panel mount computer specifically designed to be installed as an automation control interface. The ePC101WMT is widely used in many vertical manufacturing industries and by industrial OEMs.

Why Nematron?

- Internationally certified
- Unprecedented uptime
- Best in class lead times to meet your schedules and deadlines
- Long product lifecycles that help reduce your cost of ownership

Target Industries

- Automotive
- Food & beverage
- Packaging
- Power generation

Rugged, Superior Quality

- All aluminum construction
- Widescreen, multi-touch
- Solid state drives no moving parts

(intel

• Intel[®] high performance processor

Safety-Tested Reliability

- UL/cUL 60950 approved
- CE approved
- Temperature and humidity tested to 50°C
- IP65 front panel
- 2-year warranty



C€ F©

You

in







Nematron[®] ePC101WMT

PHYSICAL SPECIFICATIONS

11.22"W x 7.44"H x 1.93"D					
285mm x 189mm x 48.9mm					
10.7" x 6.92" / 272mm x 176mm 4.6 lbs. (2.1kg)					
10.1"					
1280 x 800 Widescreen					
16.2M					
350 cd/m² (NIT) Standard					
±160° Horizontal / ±160° Vertical					
Projected Capacitive Multi-touch					
800:1 (Typical)					
40,000 Hours					
Intel [®] Quad Core Celeron N2930					
Up to 2.16 GHz					
2MB					
Intel Bay Trail-M					
9-36 VDC, 4.5A-1.5A					
(Must be Powered by a Listed ITE LPS					
Power Source)					
External AC-to-DC Adapter (Universal AC Input)					

STORAGE & PERIPHERALS

JIONAOL & LINIT						
Operating System	Windows [®] 7 Professional (32-bit); Windows 7 Ultimate (64-bit), Windows 10 IoT Enterprise (32-bit or 64-bit) (optional)					
DRAM	4GB (On-board DDR3L 1333MHz Dual Channel)					
Standard Storage	150GB Solid State Drive; 240GB or 480GB Solid State Drives (optional)					
Available I/O	 (1) HDMI Port, (2) USB 2.0, (2) USB 3.0 (2) RS-232, (1) RS-232/422/485, (2) Gigabit Ethernet 10/100/1000, (1) Audio Out 					
ENCLOSURE						
Material	Die Cast Aluminum Enclosure, IP65 Compliant Aluminum Front Panel (when installed in an appropriate enclosure)					
Mounting	Panel, VESA 100 x 100					
COMPLIANCE						
Compliance	CE, FCC Class A					
Safety Agency	UL/cUL 60950 (ordinary locations) Indoor Use only					
ENVIRONMENTAL						
Operating Temperature	-0°C ~ 50°C					
Storage Temperature	-20°C ~ 60°C					
Humidity	10%~90% (Non-Condensing)					

PART NUMBER CONFIGURATOR

ePC101WMT-N2930-4GB-150SS-W7

Display Size: ——				
101WMT	10.1" Widescreen Multi-Touch			
Processor: -N2930	Intel Celeron N2930 Processor (Fanless)	 		
DRAM: -4GB	4GB DRAM			
Internal Storage -150SS -240SS -480SS	150 GB internal Solid State Drive 240 GB internal Solid State Drive 480 GB internal Solid State Drive			
Operating Syste -W7 -W7U -W1032 -W1064		 	 	





