Nematron® ePC156WMT





15.6" Widescreen, Low-Cost, Fanless, Panel Mount Industrial Computer

ePC156WMT Overview

The Nematron ePC156WMT is a high performance, fanless, panel mount computer specifically designed to be installed as an automation control interface. The ePC156WMT is widely used in many vertical manufacturing industries and by industrial OEMs.

Why Nematron?

- Internationally certified
- Unprecedented uptime
- Best in class lead times to meet your schedules and deadlines
- Long product lifecycles that help reduce your cost of ownership

Target Industries

- Automotive
- Food & beverage
- Packaging
- Power generation

Rugged, Superior Quality

- All aluminum construction
- Widescreen, multi-touch
- Solid state drives no moving parts
- Intel® high performance processor

Safety-Tested Reliability

- UL/cUL 60950 approved
- CE approved
- Temperature and humidity tested to 50°C
- IP65 front panel
- 2-year warranty



















Nematron® ePC156WMT

PHYSICAL SPECIFI	CATIONS
Dimensions (inch/mm)	16.22"W x 10.93"H x 2.37"D
	412mm x 277.5mm x 60.4mm
Cutout (inch/mm)	15.51" x 10.22" / 394mm x 259.5mm
Weight	10.58 lbs. (4.8kg)
DISPLAY SPECIFIC	ATIONS
LCD Size	15.6"
Resolution	1366 x 768 Widescreen
Display Colors	16.7M
Brightness	300 cd/m² (NIT) Standard
Viewing Angle	±160° Horizontal / ±160° Vertical
Touchscreen	Projected Capacitive Multi-Touch
Contrast ratio	500:1 (Typical)
Backlight Life	50 000 Hours

DISPLAT SPECIFICA	ATIONS
LCD Size	15.6"
Resolution	1366 x 768 Widescreen
Display Colors	16.7M
Brightness	300 cd/m² (NIT) Standard
Viewing Angle	±160° Horizontal / ±160° Vertical
Touchscreen	Projected Capacitive Multi-Touch
Contrast ratio	500:1 (Typical)
Backlight Life	50,000 Hours
PROCESSOR	

PROCESSOR	
Type & Processor	Intel® Quad Core Celeron N2930
Core Speed	Up to 2.16 GHz
L2 Cache	2MB
Chipset	Intel Bay Trail-M
POWER	
DC Input Power	9-36 VDC, 4.5A-1.5A (Must be Powered by a Listed ITE LPS Power Source)
AC Power Supply	External AC-to-DC Adapter

(Universal AC Input)

C	\sim D	$\Lambda \sim \Gamma$		DED		RALS
~ I	()K	ΔU_{-}	. ~	PFK	IPHE	·KAIS

Operating System	Windows® 7 Professional (32-bit); Windows 7 Ultimate (64-bit), Windows 10 IoT Enterprise (32-bit or 64-bit) (optional)
DRAM	4GB (On-board DDR3L 1333MHz Dual Channel)
Standard Storage	150GB Solid State Drive; 240GB or 480GB Solid State Drives (optional)
Available I/O	(1) HDMI Port, (2) USB 2.0, (2) USB 3.0, (2) RS-232, (1) RS-232/422/485, (2) Gigabit Ethernet 10/100/1000, (1) Audio Out

ENCLOSURE

Material	Die Cast Aluminum Enclosure, IP65
	Compliant Aluminum Front Panel
	(when installed in an appropriate enclosure)
Mounting	Panel, VESA 100 x 100

COMPLIANCE

C-f-t- A	
Safety Agency UL/cUL 60950 (ordinary locations) Indoor Use only	

ENVIRONMENTAL

Operating Temperature	-0°C ~ 50°C
Storage Temperature	-20°C ~ 60°C
Humidity	10%~90% (Non-Condensing)

PART NUMBER CONFIGURATOR

ePC156WMT-N2930-4GB-150SS-W7

Display Size: ——			
156WMT	15.6" Widescreen Multi-Touch		
Processor:			
-N2930	Intel Celeron N2930 Processor (Fanless)		
DRAM:			
-4GB	4GB DRAM		
Internal Storage:			
-150SS	150 GB internal Solid State Drive		
-240SS	240 GB internal Solid State Drive		
-480SS	480 GB internal Solid State Drive		
0 11 0 1			

Operating System:-

Windows 7 Professional (32-bit) -W7 -W7U Windows 7 Ultimate (64-bit) -W1032 Windows 10 IoT Enterprise (32-bit) 1 -W1064 Windows 10 IoT Enterprise (64-bit) ¹



¹ Windows 10 IoT Enterprise is the OEM equivalent to Windows 10 Professional.