
# Nematron® ePC215WMT





21.5" Widescreen, Low-Cost, Fanless, Panel Mount Industrial Computer

### ePC215WMT Overview

The Nematron ePC215WMT is a high performance, fanless, panel mount computer specifically designed to be installed as an automation control interface. The ePC215WMT is widely used in many vertical manufacturing industries and by industrial OEMs.

## Why Nematron?

- Internationally certified
- Unprecedented uptime
- Best in class lead times to meet your schedules and deadlines
- Long product lifecycles that help reduce your cost of ownership

## **Target Industries**

- Automotive
- Food & beverage
- Packaging
- Power generation

## Rugged, Superior Quality

- All aluminum construction
- Widescreen, multi-touch
- Solid state drives no moving parts
- Intel® high performance processor

## Safety-Tested Reliability

- UL/cUL 60950 approved
- CE approved
- Temperature and humidity tested to 50°C
- IP65 front panel
- 2-year warranty



















## Nematron® ePC215WMT

PHYSICAL SPECIF	ICATIONS
Dimensions (inch/mm)	21.92"W

Dimensions (inch/mm)	21.92"W x 14.25"H x 2.55"D 557mm x 362mm x 64.8mm
Cutout (inch/mm)	21.22" x 13.54" / 539mm x 344mm
Weight	17.2 lbs. (7.8kg)

#### **DISPLAY SPECIFICATIONS**

LCD Size	21.5"
Resolution	1920 x 1080 Widescreen
Display Colors	16.7M
Brightness	250 cd/m² (NIT) Standard
Viewing Angle	±178° Horizontal / ±178° Vertical
Touchscreen	Projected Capacitive Multi-Touch
Contrast ratio	3000:1 (Typical)
Backlight Life	50,000 Hours

#### **PROCESSOR**

INOCESSOR	
Type & Processor	Intel® Quad Core Celeron N2930
Core Speed	Up to 2.16 GHz
L2 Cache	2MB
Chipset	Intel Bay Trail-M

Chipset litter bay Iran-Ivi		
POWER		
DC Input Power	9-36 VDC, 4.5A-1.5A (Must be Powered by a Listed ITE LPS Power Source)	
AC Power Supply	External AC-to-DC Adapter (Universal AC Input)	

#### **STORAGE & PERIPHERALS**

Operating System	Windows® 7 Professional (32-bit); Windows 7 Ultimate (64-bit), Windows 10 IoT Enterprise (32-bit or 64-bit) (optional)
DRAM	4GB (On-board DDR3L 1333MHz Dual Channel)
Standard Storage	150GB Solid State Drive; 240GB or 480GB Solid State Drives (optional)
Available I/O	(1) HDMI Port, (2) USB 2.0, (2) USB 3.0, (2) RS-232, (1) RS-232/422/485, (2) Gigabit Ethernet 10/100/1000, (1) Audio Out

#### **ENCLOSURE**

Material	Die Cast Aluminum Enclosure, IP65 Compliant Aluminum Front Panel
	(when installed in an appropriate enclosure)
Mounting	Panel, VESA 100 x 100

#### **COMPLIANCE**

Compliance	CE, FCC Class A
Safety Agency	UL/cUL 60950 (ordinary locations)
	Indoor Use only

#### **ENVIRONMENTAL**

Operating Temperature	-0°C ~ 50°C
Storage Temperature	-20°C ~ 60°C
Humidity	10%~90% (Non-Condensing)

#### PART NUMBER CONFIGURATOR

## ePC215WMT-N2930-4GB-150SS-W7

Display Size: ——				
215WMT	21.5" Widescreen Multi-Touch			
Processor:——				
-N2930	Intel Celeron N2930 Processor (Fanless)			
DRAM:				
-4GB	4GB DRAM			
Internal Storage:				
-150SS	150 GB internal Solid State Drive			
-240SS	240 GB internal Solid State Drive			
-480SS	480 GB internal Solid State Drive			

#### **Operating System:-**

-W7 Windows 7 Professional (32-bit) -W7U Windows 7 Ultimate (64-bit) -W1032 Windows 10 IoT Enterprise (32-bit) 1 -W1064 Windows 10 IoT Enterprise (64-bit) <sup>1</sup>



<sup>&</sup>lt;sup>1</sup> Windows 10 IoT Enterprise is the OEM equivalent to Windows 10 Professional.