

## PNOZ m B1

772101




Configurable control system PNOZmulti 2 base module expandable, communication interface, 2 Ethernet interfaces, USB memory.

### Technical details

Certifications:	CE;cULus Listed;EAC (Eurasian);TÜV;KOSHA
Number of test pulse outputs:	4
Power consumption DC:	18.5 W
Supply voltage (V):	24,0
Supply voltage type:	DC
Base unit:	Yes
Terminal type:	Cage clamp terminal;Screw terminal
Terminal style:	Plug-in
Version for extreme environ. conditions:	Standard
Width dimension:	45.0 mm
Height dimension:	101.4 mm
Depth dimension:	120.2 mm
Gross weight:	219 g
Net weight:	209 g
Ambient temperature:	0 - 60 °C

### Accessories



773010B

Basic Licence for PNOZmulti Config.



751016

Set4 Spring Terminals



750016

Set4 Screw Terminals

## Optional accessories



380401

RJ45 Connector



773010K

User Licence for PNOZmulti Config



773010U

Basic Upgr Licence for PNOZmulti Config




773011B

Basic Licence for PNOZmulti Service



773011K

User Licence for PNOZmulti Service



773011U

Basic Upgr Licence for PNOZmulti Service



773011V

User Upgr Licence for PNOZmulti Service



779213

USB Memory 512MB

## Alternatives



772100

PNOZ m B0

## Related Products



773616

PDP67 F 8DI ION PT



773615

PDP67 F 8DI ION HP VA



773614

PDP67 F 8DI ION VA



773601

PDP67 F 8DI ION HP



773600

PDP67 F 8DI ION



772181

PNOZ m ES 14DO

---



772171

PNOZ m EF 2MM

---



772170

PNOZ m EF 1MM

---



772160

PNOZ m EF 4AI

---



772144

PNOZ m EF 8DI2DOT

---



772143

PNOZ m EF 4DI4DOR

---



772142

PNOZ m EF 8DI4DO

---



772140

PNOZ m EF 16DI

---



772138

PNOZ m ES Profinet

---



772137

PNOZ m ES EtherNet/IP

---



772136

PNOZ m ES EtherCAT

---



772135

PNOZ m ES CC-Link

---



772134

PNOZ m ES CANopen

---



772132

PNOZ m ES Profibus

---



772122

PNOZ m EF SafetyNET

---



772121

PNOZ m EF PDP Link

---



772120

PNOZ m EF Multi Link

---



772119

PNOZ m ES Powerlink

---