

PSEN cs4.1p 1switch

541160



RFID safety switch 2 safe semiconductor outputs, 8-pin M8 connector, one direction of actuation IP67, operating distance 11 mm, Sao = 8 mm, Sar = 20 mm, PU = 1 piece fully coded switch without actuator, A total of 8 learning procedures are possible.

Technical details

| | |
|-----------------------------|-------------------------------------------|
| Certifications: | CE;cULus Listed;EAC (Eurasian);TÜV;FCC;IC |
| Sensor principle: | Transponder |
| Type of coding: | Fully coded |
| Number of OSSD outputs: | 2 |
| Number of inputs: | 2 |
| Connection type: | M8, 8pol. male |
| Supply voltage (V): | 24,0 |
| Supply voltage type: | DC |
| Power consumption DC: | 1.0 W |
| Assured switching distance: | 8.0 mm |
| Assured release distance: | 20.0 mm |
| Protection type, housing: | IP6K9K |
| Width dimension: | 26.0 mm |
| Height dimension: | 37.0 mm |
| Depth dimension: | 18.0 mm |
| Gross weight: | 50 g |
| Net weight: | 30 g |
| Ambient temperature: | -25 - 70 °C |

Accessories

| | | |
|-------------------------------------------------------------------------------------|--------|-----------------------------------------|
|  | 533150 | PSEN cable M8-8sf, 2m |
|  | 533151 | PSEN cable M8-8sf, 5m |
|  | 533152 | PSEN cable M8-8sf, 10m |
|  | 533153 | PSEN cable M8-8sf, 20m |
|  | 533154 | PSEN cable M8-8sf, 30m |
|  | 540180 | PSEN cs2.1 1 actuator |
|  | 541180 | PSEN cs4.1 1 actuator |
|  | 541187 | PSEN cs4.1 low profile glue 1 actuator |
|  | 541188 | PSEN cs4.1 low profile screw 1 actuator |

Optional accessories



533150

PSEN cable M8-8sf, 2m



533151

PSEN cable M8-8sf, 5m



533152

PSEN cable M8-8sf, 10m



533153

PSEN cable M8-8sf, 20m



533154

PSEN cable M8-8sf, 30m



533155

PSEN cable M8-8sf M8-sm, 0.5m




533156

PSEN cable M8-8sf M8-8sm, 1m



533157

PSEN cable M8-8sf M8-8sm, 2m



540329

PSEN converter M8-8sf -- M12-8sm



773603

PDP67 F 4 code



540340

PSEN cable M12-8sf M12-8sm, 2m



540341

PSEN cable M12-8sf M12-8sm, 5m



540343

PSEN cable M12-8sf M12-8sm, 20m



540344

PSEN cable M12-8sf M12-8sm, 30m



540342

PSEN cable M12-8sf M12-8sm, 10m



540130

SDD ES ETH



540132

SDD ES PROFIBUS



540337

PSEN Y junction M8-M12/M12 PIGTAIL