



NIPF7.E244656

Active Opto-electronic Protective Devices Certified for Canada

[Page Bottom](#)

Active Opto-electronic Protective Devices Certified for Canada

[See General Information for Active Opto-electronic Protective Devices Certified for Canada](#)

PILZ GMBH & CO KG

E244656

FELIX WANKEL STRASSE 2
73760 OSTFILDERN 2, GERMANY

Type 2 and Type 4 Light curtains, Series PSEN followed by op, opSB, followed by 4F, 4H, 4B, 2B, followed by b, bm, m, s, sl, L, S, T or none, followed by 2, 3, 4, 5, 14, 20, 30, followed by 015 through 180.

Series PSEN; followed by op2H or op4F or op4H, followed by A or s; followed by 14 or 30; followed by 015 thru 180; followed by /1.

Models PSEN op4F-s-14-015/1, PSEN op4F-s-14-030/1, PSEN op4F-s-14-045/1, PSEN op4F-s-14-060/1, PSEN op4F-s-14-075/1, PSEN op4F-s-14-090/1, PSEN op4F-s-14-105/1, PSEN op4F-s-14-120/1, PSEN op4F-s-14-135/1, PSEN op4F-s-14-150/1, PSEN op4F-s-14-165/1, PSEN op4F-s-14-180/1, PSEN op4H-s-30-015/1, PSEN op4H-s-30-030/1, PSEN op4H-s-30-045/1, PSEN op4H-s-30-060/1, PSEN op4H-s-30-075/1, PSEN op4H-s-30-090/1, PSEN op4H-s-30-105/1, PSEN op4H-s-30-120/1, PSEN op4H-s-30-135/1, PSEN op4H-s-30-150/1, PSEN op4H-s-30-165/1, PSEN op4H-s-30-180/1, PSEN op2H-s-30-015/1, PSEN op2H-s-30-030/1, PSEN op2H-s-30-045/1, PSEN op2H-s-30-060/1, PSEN op2H-s-30-075/1, PSEN op2H-s-30-090/1, PSEN op2H-s-30-105/1, PSEN op2H-s-30-120/1, PSEN op2H-s-30-135/1, PSEN op2H-s-30-150/1, PSEN op2H-s-30-165/1, PSEN op2H-s-30-180/1, PSEN op2H-A-30-030/1, PSEN op2H-A-30-045/1, PSEN op2H-A-30-060/1, PSEN op2H-A-30-075/1, PSEN op2H-A-30-090/1, PSEN op2H-A-30-105/1, PSEN op2H-A-30-120/1, PSEN op2H-A-30-135/1, PSEN op2H-A-30-150/1, PSEN op2H-A-30-165/1, PSEN op2H-A-30-180/1, PSEN op4F-A-14-030/1, PSEN op4F-A-14-045/1, PSEN op4F-A-14-060/1, PSEN op4F-A-14-075/1, PSEN op4F-A-14-090/1, PSEN op4F-A-14-105/1, PSEN op4F-A-14-120/1, PSEN op4F-A-14-135/1, PSEN op4F-A-14-150/1, PSEN op4F-A-14-165/1, PSEN op4F-A-14-180/1, PSEN op4H-A-30-030/1, PSEN op4H-A-30-045/1, PSEN op4H-A-30-060/1, PSEN op4H-A-30-075/1, PSEN op4H-A-30-090/1, PSEN op4H-A-30-105/1, PSEN op4H-A-30-120/1, PSEN op4H-A-30-135/1, PSEN op4H-A-30-150/1, PSEN op4H-A-30-165/1, PSEN op4H-A-30-180/1, PSEN op2B-2-050/1, PSEN op2B-3-080/1, PSEN op2B-4-090/1, PSEN op2B-4-120/1, PSEN op2B-L-050/1, PSEN op2B-L-080/1, PSEN op2B-T-050/1, PSEN op2B-T-080/1, PSEN op4B-2-050/1, PSEN op4B-3-080/1, PSEN op4B-4-090/1, PSEN op4B-4-120/1, PSEN op4B-L-050/1, PSEN op4B-L-080/1, PSEN op4B-T-050/1, PSEN op4B-T-080/1, PSEN op4F-SL-14-015/1, PSEN op4F-SL-14-021/1, PSEN op4F-SL-14-030/1, PSEN op4F-SL-14-036/1, PSEN op4F-SL-14-042/1, PSEN op4F-SL-14-045/1, PSEN op4F-SL-14-048/1, PSEN op4F-SL-14-054/1, PSEN op4F-SL-14-060/1, PSEN op4F-SL-14-066/1, PSEN op4F-SL-14-072/1, PSEN op4F-SL-14-075/1, PSEN op4F-SL-14-078/1, PSEN op4F-SL-14-084/1, PSEN op4F-SL-14-090/1, PSEN op4F-SL-14-096/1, PSEN op4F-SL-14-102/1, PSEN op4F-SL-14-105/1, PSEN op4F-SL-14-108/1, PSEN op4F-SL-14-114/1, PSEN op4F-SL-14-120/1, PSEN op4H-SL-24-015/1, PSEN op4H-SL-24-030/1, PSEN op4H-SL-24-045/1, PSEN op4H-SL-24-060/1, PSEN op4H-SL-24-075/1, PSEN op4H-SL-24-090/1, PSEN op4H-SL-24-105/1, PSEN op4H-SL-24-120/1, PSEN op2H-SL-24-015/1, PSEN op2H-SL-24-030/1, PSEN op2H-SL-24-045/1, PSEN op2H-SL-24-060/1, PSEN op2H-SL-24-075/1, PSEN op2H-SL-24-090/1, PSEN op2H-SL-24-105/1, PSEN op2H-SL-24-120/1.

Type 2 Light curtain, Series PSEN op2H followed by 30, followed by 015 through 180.

Type 4 Light curtain, Models PSEN opII; followed by 4; followed by F or H; followed by -S; followed by -14 or -30; followed by 015 through 180.

[Last Updated](#) on 2016-10-25

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2016 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2016 UL LLC".