

NT24k[®]-DR24 Modular Industrial Switch

N-Tron[®] Networking Series



Managed Gigabit Industrial Ethernet Switch

The N-Tron[®] series NT24k[®]-DR24 is a modular managed switch designed for factory automation, utilities, security surveillance, SCADA and other industrial applications.

The Red Lion N-Tron series NT24k-DR24 managed industrial Ethernet switch features connectivity for up to 24 Gigabit ports and offers a wide range of connectivity options—including 100Base, Gigabit, fiber optic and copper options—in a rugged DIN-rail mountable enclosure. Designed to handle the most demanding environments, the NT24k-DR24 delivers wire-speed throughput and includes expanded shock and vibration tolerances, extreme operating temperature range and three slots to accommodate mix-and-match port modules. N-Ring[™] technology restores network communication within ~30ms of fault detection. Robust remote monitoring capabilities make management easy.



APPLICATIONS

- > Factory Automation
- > Utilities
- > SCADA
- > Security Surveillance
- > Transportation
- > Alternative Energy

PRODUCT HIGHLIGHTS

- > All Gigabit Modular Design
- > Up to 24 Port Connections
- > High Environmental Specifications
- > N-Ring[™] Advanced Ring Technology
- > Robust Remote Monitoring
- > Smart Plug-and-Play Operation

IEEE 1588v2 PTP OPTIONS

- Boundary Clock
 - Transparent Clock
- IEEE 1588v2 applications include
- Coordinated motion control
 - Time-stamped data logging
 - Time-stamped fault detection

PTP Models & Upgrade Kit Available

FEATURES & BENEFITS

- > Supports up to three of the following port modules:
 - 8-port 10/100/1000BaseT(X) module
 - 8-port 100Base fiber module
 - 8-port 1000Base fiber module
 - 8-port Gigabit SFP module
 - 8-port dual mode SFP module (100Base or 1000Base SFP transceivers)
- > -40°C to 75°C operating temperature
- > Power input selections:
 - Low Voltage: 18-49 VDC
 - High Voltage: 90-264 VAC or 90-300 VDC
- > Onboard temperature sensor
- > ESD and surge protection diodes on all copper ports
- > Auto-sensing 10/100/1000BaseT(X), duplex and MDIX
- > USB configuration port
- > Configurable alarm contact
- > Optional backup/restore configuration device
- > Fully managed features include:
 - SSH/SSL/HTTPS
 - SNMP v1, v2, v3
 - Web browser management
 - Detailed ring map and fault location charting
 - RSTP - 802.1d, 802.1w, 802.1D
 - Trunking and port mirroring
 - 802.1Q tag VLAN and port VLAN
 - IEEE 802.1x with RADIUS remote server authentication
 - DHCP Server, Option 82 relay, Option 61, IP fallback
 - Port Security – MAC address based
 - 802.1p QoS, port QoS and DSCP
 - Event Log/Syslog
 - SNTP (Simple Network Time Protocol)
 - IEEE 1588v2 (PTP) models available
 - Multi-Member N-Ring[™] technology with ~30ms healing
 - N-Link redundant ring technology
 - N-View[™] monitoring technology
 - EtherNet/IP[™] CIP[™] messaging
 - 802.1AB-2005 LLDP (Link Layer Discovery Protocol)

industrial
networking



EtherNet/IP[™]

Managed Gigabit Industrial Ethernet Switch Specifications

SWITCH PROPERTIES

Number of MAC Addresses: 16K
 IEEE 1588v2 Software-Based Option
 Aging Time: Programmable
 Latency (typical): 1.6 μ s
 Switching Method: Store & Forward
 MTBF: >1 million hours
 Jumbo Frame Support

POWER INPUT OPTIONS

Select one:
 Low Voltage: 18-49 VDC
 High Voltage: 90-264 VAC or 90-300 VDC
 Input Current (max): 2.14A @ 24VDC
 Input Current (max): 780mA @120 VAC/430mA @ 124VDC
 BTU/hr: 175 @ 24VDC
 BTU/hr: 360 @ 120VAC/182 @ 124VDC

CONNECTORS

10/100/1000BaseT(X): Up to 24 RJ45 copper ports
 100BaseFX: Up to 24 SC or ST fiber ports
 1000BaseFX: Up to 24 SC fiber ports
 100BaseSX/LX SFP: Up to 24 LC fiber ports
 1000BaseGX SFP: Up to 24 LC fiber ports

NETWORK MEDIA

10BaseT: \geq Cat3 cable
 100BaseTX: \geq Cat5 cable
 1000BaseT: \geq Cat5 cable
 100BaseFX, 1000BaseSX Multimode: 50-62.5/125 μ m
 100BaseFX, 1000BaseLX Singlemode: 7-10/125 μ m

RECOMMENDED WIRING CLEARANCE

Front and Top: 4" (10.2 cm)

CERTIFICATION & COMPLIANCE

Product Safety:
 ANSI/ISA 12.12.01-2013 Class I and II, Div. 2 and Class III, Div. 1 and 2, Groups A, B, C and D Hazardous Locations
 UL508 Industrial Control Equipment
 CAN/CSA-C22.2 No. 213-M1987 Class I Div. 2 Hazardous Locations
 CAN/CSA-C22.2 No. 14-M1987 Industrial Control Equipment
 Emissions:
 FCC Title 47, Part 15, Radio Frequency Devices, Subpart B ANSI C63.4-2009; Industry Canada ICES-003, EN 55011; EN 61000-6-4, EN 61000-3-2, EN61000-3-3, EN 55032
 Immunity:
 EN 55024, EN 61000-6-2; IEC 61000-4-2 (ESD); IEC 61000-4-3 (RFAM); IEC 61000-4-4 (EFT); IEC 61000-4-5 (SURGE); IEC 61000-4-6 (RFCM); IEC 61000-4-8 (PFMF); IEC 61000-4-11 (VDI)
 Other:
 ABS Type Approval for Shipboard Applications; EMC Directive 2014/30/EU; LV Directive 2014/35/EU GOST-R, RoHS Compliant


ENVIRONMENTAL

Operating Temperature: -40° C to 75° C
 Operating Humidity: 5% to 95% (Non Condensing)
 Operating Altitude: 0 to 10,000 ft.
 Shock: 50g @ 10ms
 Vibration/Seismic: 30g, 10-200 Hz, triaxial

MECHANICAL

Case Dimensions
 Height: 5.97" (15.20 cm)
 Width: 8.45" (21.46 cm)
 Depth: 4.59" (11.65 cm)
 Weight (maximum): 7.8 lbs (3.54 kg)
 Mount: DIN rail

DIMENSIONS



Managed Gigabit Industrial Ethernet Switch Specifications

NT24K-FX8 MODULE - 100 MB FIBER TRANSCEIVER CHARACTERISTICS

Fiber Mode	MM	SM	SM	SM
Fiber Length*	2km	15km	40km	80km
TX Power Min	-19 dBm	-15 dBm	-5 dBm	-5 dBm
RX Sensitivity Max	-31 dBm	-31 dBm	-34 dBm	-34 dBm
Wavelength	1310 nm	1310 nm	1310 nm	1550 nm

NT24K-GX8 MODULE - GIGABIT FIBER TRANSCEIVER CHARACTERISTICS

Fiber Mode	MM	SM	SM	SM
Fiber Length*	550m @ 50/125µm 300m @ 62.5/125µm	10km	40km	80km
TX Power Min	-9.5 dBm	-9.5 dBm	-5 dBm	0 dBm
RX Sensitivity Max	-17 dBm	-20 dBm	-23 dBm	-24 dBm
Wavelength	850 nm	1310 nm	1310 nm	1550 nm
Laser Type	VCSEL	FP	DFB	DFB

NT24K-SFP-DM8 MODULE - SFP 100BASE FIBER TRANSCEIVER CHARACTERISTICS

Fiber Mode	MM	SM	SM	SM
Fiber Length*	2km	15km	40km	80km
TX Power Min	-19 dBm	-15 dBm	-5 dBm	-5 dBm
RX Sensitivity Max	-31 dBm	-34 dBm	-34 dBm	-34 dBm
Wavelength	1310 nm	1310 nm	1310 nm	1550 nm
Laser Type	FP	FP	FP	DFB

NT24K-SFP-DM8 OR NT24K-SFP8 MODULES- SFP GIGABIT FIBER TRANSCEIVER CHARACTERISTICS

Fiber Mode	MM	SM	SM	SM
Fiber Length*	550m @ 50/125µm 275m @ 62.5/125µm	10km	40km	80km
TX Power Min	-9.5 dBm	-9.5 dBm	-2 dBm	0 dBm
RX Sensitivity Max	-17 dBm	-20 dBm	-22 dBm	-24 dBm
Wavelength	850 nm	1310 nm	1310 nm	1550 nm
Laser Type	VCSEL	FP	DFB	DFB

* Fiber Length distances represent typical performance.
Link budgets should be evaluated based on specific application conditions.

ORDERING GUIDE

PART NUMBER	DESCRIPTION
NT24K-DR24-DC	Managed Industrial Ethernet Switch; modular DIN rail design with 3 expansion slots; redundant 18-49VDC power input
NT24K-DR24-DC-PT	Managed Industrial Ethernet Switch; modular DIN rail design with 3 expansion slots; redundant 18-49VDC power input PTP Enabled
NT24K-DR24-AC	Managed Industrial Ethernet Switch; modular DIN rail design with 3 expansion slots; 90-264VAC / 90-300VDC power inputs
NT24K-DR24-AC-PT	Managed Industrial Ethernet Switch; modular DIN rail design with 3 expansion slots; 90-264VAC / 90-300VDC power inputs PTP Enabled
NT24K-FP	Filler panel (required to fill vacant module slots)
NTCD-CFG	Configuration recovery device
NTPC-AC-US	AC power cord
NTPS-24-3	DIN rail power supply 3.0 Amp @ 24 VDC
NT24K-DR-PMK	NT24k DR panel mount kit
NT24K-KIT-PTP	NT24k Upgrade License to Enable IEEE 1588/PTP on Non-PT NT24k Switches
PORT MODULES & TRANSCEIVERS	
NT24K-TX8	8-port 10/100/1000BaseT module
NT24K-FX8-XX	Slide-in module with 8 100BaseFX multimode fiber ports, 2km (SC or ST)
NT24K-FXE8-XX-YY	Slide-in module with 8 100BaseFX singlemode fiber ports (SC or ST)
NT24K-GX8-SC	Slide-in module with 8 1000BaseFX multimode fiber ports, 550m (SC)
NT24K-GXE8-SC-ZZ	Slide-in module with 8 1000BaseFX singlemode fiber ports (SC)
NT24K-SFP8	Slide-in module with 8 SFP expansion slots; supports 1000Base SFP transceivers*
NT24K-SFP-DM8	Slide-in module with 8 dual mode SFP expansion slots; supports 100Base or 1000Base SFP transceivers*
NTSFP-FX	100BaseFX multimode fiber SFP pluggable mini-GBIC transceiver (LC style connector, 2km)**
NTSFP-FXE-YY	100BaseFX singlemode fiber SFP pluggable mini-GBIC transceiver (LC style connector)**
NTSFP-TX	1000BaseT copper SFP pluggable mini-GBIC transceiver
NTSFP-SX	1000BaseSX multimode fiber SFP pluggable mini-GBIC transceiver
NTSFP-LX-ZZ	1000BaseLX singlemode fiber SFP pluggable mini-GBIC transceiver

Where: XX = ST or SC connector (ST not available on some GX modules); YY = 15, 40, or 80 for FX singlemode, blank for multimode; ZZ = 10, 40, or 80 for GX singlemode; *SFP transceivers sold separately; **For use with SFP DM8 module only



Americas
sales@redlion.net

Asia-Pacific
asia@redlion.net

**Europe
Middle East
Africa**
europe@redlion.net
+1 (717) 767-6511

As the global experts in communication, monitoring and control for industrial automation and networking, Red Lion has been delivering innovative solutions for over forty years. Our award-winning technology enables companies worldwide to gain real-time data visibility that drives productivity. Product brands include Red Lion, N-Tron and Sixnet. With headquarters in York, Pennsylvania, the company has offices across the Americas, Asia-Pacific and Europe. For more information, please visit www.redlion.net. Red Lion is a Spectris company.

ADLD0333 0601119 © 2019 Red Lion Controls, Inc. All rights reserved. Red Lion, the Red Lion logo, N-Tron and Sixnet are registered trademarks of Red Lion Controls, Inc. All other company and product names are trademarks of their respective owners.