

Gigabit 1000-POE+ Injector

N-Tron Networking Series



▶▶▶ Gigabit Mid-Span Power Over Ethernet Plus (PoE+)

The industrial Gigabit 1000-POE+ injector simplifies network deployments by providing a robust solution for transmitting power and data to industrial assets.

Red Lion's N-Tron series 1000-POE+ simplifies network device deployment by combining Gigabit data communications and power over a single Ethernet network cable. Ideal for deployment in industrial networks including oil and gas, water/wastewater, utility, transportation, mining and factory floor applications, the 1000-POE+ provides auto-sensing plug-and-play performance to PoE+ devices like video cameras and network switches. The 1000-POE+ enables customers to save deployment space and installation time by reducing network complexity.



APPLICATIONS

- > Oil & Gas
- > Water/Wastewater
- > Utility
- > Transportation
- > Mining
- > Manufacturing

PRODUCT HIGHLIGHTS

- > IEEE802.3af/at PoE+
- > Gigabit Network Performance
- > 10 to 30 VDC Power Input
- > LED Status Indicators

FEATURES & BENEFITS

- > IEEE802.3af/at Compliant
 - Provides up to 30 watts of power
- > Gigabit Ethernet Speed
 - Ideal for bandwidth intensive applications
 - Jumbo frame support
- > Redundant 10 to 30 VDC Power Input
 - Keeps PoE devices running in the event of a power supply failure
- > Rugged Compact Design
 - Perfect for space-constrained applications
- > Extended Environmental Specifications
 - -40° to 80°C operating temperature range
- > LED Status Lights
 - Display power and connectivity conditions

industrial
networking



▶▶▶ 1000-POE+ Specifications

SWITCH PROPERTIES

IEEE 802.3af/at Compliant
One 10/100/1000Base-TX RJ-45 Port (Data In)
One 10/100/1000Base-TX RJ-45 POE+ Port (Data & Power Out)
Unmanaged Operation
Supports 30 Watts per Port (25.5 Watts at the PD)
Up to 1.0 Gb/s Maximum Throughput
Full Wire Speed Communications
Power Status LED
POE Status Indication LED
Hardened Metal DIN-Rail Mountable Enclosure
MTBF: > 2 million hours

POWER INPUT

Input Voltage: 10-30 VDC
Input Current (Max): 1.32 A @ 24 VDC
Inrush: 22.0 A/2.1ms @ 24 VDC

POWER OVER ETHERNET

PoE Standard: IEEE 802.3af/at Gigabit/ Mid-span PSE
PoE Output Power: 54 VDC / 30 Watts Output (25.5W at PD)
PSE Type: Type 2

CONNECTORS

10/100/1000Base-T(X): Two (2) RJ-45 TX Copper Ports

NETWORK MEDIA

10Base-T: >Cat3 Cable
100Base-TX: >Cat5 Cable
1000Base-T: >Cat5e Cable

RECOMMENDED WIRING CLEARANCE

Front: 2"
Top: 1"

CERTIFICATION & COMPLIANCE

Product Safety: USA UL 508; ANSI/ISA-12.12.01-2013, Class I and II, Division 2 and Class III, Divisions 1 and 2 Groups A, B, C and D Hazardous Locations; Canada C22.2 No. 14; C22.2 No. 213-M1987 Class I, Division 2 Hazardous Locations; Temperature Code T4A
EMI/EMC: FCC 47 CFR, Part 15, Subpart B; Industry Canada ICES-003 Issue 5; ANSI C63.4-2009; CE; EMC Directive 2004/108/EC; Immunity EN 61000-6-2:2005; Emissions EN 61000-6-4:2007; EN55011:2009+A1:2010; IEC 61000-4-2/3/4/5/6/8
Rail: EN 50155, EN 50121 and EN 61373
Other: ABS Type Approval for Shipboard Applications; GOST-R certified; RoHS compliant

DESIGNED TO COMPLY WITH

IEEE 1613 for Electric Utility Substations
NEMA TS1/TS2 for Traffic Control


ENVIRONMENTAL

Operating Temperature: -40° to +80°C
Operating Altitude: 0 to 10,000 ft.
Shock: IEC60068-2-27
Vibration: IEC60068-2-6
Humidity: 5 to 95% non-condensing

MECHANICAL

Height: 4.30" (10.92 cm)
Width: 1.00" (2.54 cm)
Depth: 3.63" (9.22 cm)
Including DIN-Rail Mount: 3.83" (9.73 cm)
Weight: 0.6 lbs. (0.27 kg)
DIN-Rail: 35 mm

DIMENSIONS



www.redlion.net

Connect. Monitor. Control.

Americas
sales@redlion.net

Asia-Pacific
asia@redlion.net

**Europe
Middle East
Africa**
europe@redlion.net

+1 (717) 767-6511

As the global experts in communication, monitoring and control for industrial automation and networking, Red Lion has been delivering innovative solutions for over forty years. Our automation, Ethernet and cellular M2M technology enables companies worldwide to gain real-time data visibility that drives productivity. Product brands include Red Lion, N-Tron and Sixnet. With headquarters in York, Pennsylvania, the company has offices across the Americas, Asia-Pacific and Europe. Red Lion is part of Spectris plc, the productivity-enhancing instrumentation and controls company. For more information, please visit www.redlion.net.

ADLD0385 012918 © 2018 Red Lion Controls, Inc. All rights reserved. Red Lion, the Red Lion logo, N-Tron and Sixnet are registered trademarks of Red Lion Controls, Inc. All other company and product names are trademarks of their respective owners.