



MIL-STD
810G

IP54

MOTION® BY XPLORE™ C5m TABLET PC



PRODUCT SPECIFICATIONS

PROCESSOR / CACHE	<ul style="list-style-type: none"> Intel® Core™ i7 vPro™ Processor 2.6 GHz 5600U with Turbo Boost to 3.2 GHz (4MB of L3 cache, 2 Cores/4 Threads) or Intel® Core™ i5 Processor 2.2 GHz 5200U with Turbo Boost to 2.7 GHz (3MB of L3 cache, 2 Cores/4 Threads) 	SYSTEM MEMORY	<ul style="list-style-type: none"> DDR3L 1600MHz SDRAM memory Base configuration of 4GB Optional configuration of 8GB or 16GB
OPERATING SYSTEM	<ul style="list-style-type: none"> Windows® 10 64-bit Windows® 8.1 Pro Windows® 7 Professional 64-bit 	SYSTEM STORAGE	<ul style="list-style-type: none"> m.2 Solid State Drive (SSD) with capacities of 64GB, 128GB or 256GB m.2 Self-encrypting drives (SED) with capacity of 256 GB (optional)* AHCI
DURABILITY	<ul style="list-style-type: none"> Meets MIL-STD-810G IP54 rated - Water, dust and splash resistant Class 1 Division 2 certified (optional configuration) Durable Gorilla® Glass Rubberized for shock dampening Magnesium-alloy internal frame Molded handle helps prevent drops 	INTEGRATED COMMUNICATIONS	<ul style="list-style-type: none"> IEEE 802.11ac Wi-Fi® plus Bluetooth® 4.0 Optional Integrated Mobile Broadband <ul style="list-style-type: none"> - Qualcomm® Gobi™ technology 4G LTE** Mobile Broadband with either <ul style="list-style-type: none"> o GNSS (GPS + GLONASS) o Optional U-Blox 7 GPS
DISPLAY	<ul style="list-style-type: none"> 10.4" XGA (1024 x 768) View Anywhere® Display with Projective Capacitive 10-point Touch TFT AFFS+ LED Backlight with Durable Gorilla® Glass or 10.4" XGA (1024 x 768) Standard Display with Projective Capacitive 10-point Touch TFT AFFS+ LED Backlight with Durable Gorilla® Glass Intel Display Power Saving Technology (DPST) 	AUDIO	<ul style="list-style-type: none"> Noise cancellation technology Multi-directional array microphone design with 2 microphones Integrated speaker
GRAPHICS	<ul style="list-style-type: none"> Intel® HD Graphics 5500 GT2 Rotation: 0°, 90°, 270° 	I/O PORTS	<ul style="list-style-type: none"> Docking connector USB 3.0 port with rubberized cover
AUDIO CONTROLLER	<ul style="list-style-type: none"> High Definition Audio 	EMBEDDED I/O	<ul style="list-style-type: none"> 8.0 Megapixel camera (rear-facing) 2.0 Megapixel front-facing web camera Optional 1D/2D Barcode Reader
		SECURITY	<ul style="list-style-type: none"> Integrated Fingerprint Reader with OmniPass software TCG Trusted Platform Module (TPM) 1.2 Smart card reader (optional) <ul style="list-style-type: none"> - ISO 7816 PC/SC - EMV2 2000 Level 1 Computrace® Complete (optional)
		DIMENSIONS	<ul style="list-style-type: none"> 10.0" x 10.0" x .95" (256mm x 256mm x 24.3mm)
		WEIGHT	<ul style="list-style-type: none"> 3.3 lbs.¹ (1.50 kg)
		BATTERY	<ul style="list-style-type: none"> Battery life over 8 hours² Hot swappable Lithium Ion standard battery with 40Whr capacity
		BATTERY CHARGING TIME	<ul style="list-style-type: none"> Standard Battery - 1.5 hours (Tablet PC on/off)³

AC ADAPTER

- 65W universal, 3-pin jack
- 100-240V 1.5A, 50-60Hz

SOFTWARE

- Windows® 7 Software
- SnapWorks® by Motion Camera App
 - Barcode Reader
 - Motion/Softex OmniPass™ Security Software
 - Motion Dashboard Control Panel
 - Mobile Broadband Connection Manager
 - Pen and Touch Enabled BIOS Setup
 - Infineon Security Platform Tools (Optional)

- Windows® 8 Software / Windows® 10 Software
- SnapWorks® by Motion
 - Barcode Reader
 - Motion/Softex OmniPass™ Security Software
 - Motion Tablet Center
 - Know Your Motion Tablet
 - Pen and Touch Enabled BIOS Setup
 - Infineon Security Platform Tools (Optional)

SYSTEM STATUS LED

- Power on/off/stand by LED ring around power button
- Battery status LED on back
- Battery charge gauge on front

CONTROL BUTTONS

- One 5-way directional for navigation
- One function, one Dashboard and two programmable
- Secure Attention Sequence (SAS)
- Volume controls
- Windows Home button
- Barcode scan trigger (programmed)

BUILT-IN CAMERAS

Rear-Facing Camera

- Autofocus
- 8.0 megapixel resolution
- Illuminator light

Front-Facing Camera

- Autofocus
- 2.0 megapixel resolution

ENVIRONMENTAL

- MIL-STD-810G Certified (4' Drop, Altitude, -51°C to 71°C Storage Temperature, -10°C to 55°C Operating Temperature, Temperature Shock, Rain, Humidity, Sand and Dust, Vibration, Shock)
- Class I Division 2 certified, Groups ABCD (optional configuration)
- EU Directive RoHS 2 (2011/05/EU)
- EU Directive ErP (2009/125/EC)
- EU Directive WEEE (2012/19/EC)

WARRANTY

- 3-year standard warranty

STANDARDS

- ACPI 3.0b compliant

SAFETY

- AS/NZS 60950-1
- Class I Division 2 certified (optional configuration)
- FCC/ANSI C63.41
- IC RSS 102
- ETSI EN 62311
- UL, CUL, CE (IEC/EN60950-1 A11/2004)
- EU Directive LVD (2006/95/EC)
- EU Directive Batteries (2006/66/EC and its amendments)
- California Proposition 65
- Technical Instructions for Safe Transport of Dangerous Goods by Air (ICAO Doc #9284)
- Emergency Response Guidance for Aircraft incidents involving Dangerous Goods (ICAO Doc #9481)

REGULATORY

- AS/NZS 3548:1995 Class B
- AS/NZS 4268
- AS/ACIF S042.1 (WCDMA/HSDPA)
- AS/ACIF S042.3 (WCDMA/HSDPA)
- AS/ACIF S042.1 (GSM/EDGE)
- AS/ACIF S042.3 (GSM/EDGE)
- CAN/CSA ICES-003 Class B
- CAN/CSA RSS-210 Issue 5
- CAN/CSA RSS-310 Issue 2
- CAN/CSA RSS-132 (1xRTT/EVDO-0/EVDO-A)
- CAN/CSA RSS-133 (1xRTT/EVDO-0/EVDO-A)
- CENELEC EN 60601-1-2
- CENELEC EN 55022 Class B (CISPR22)
- CENELEC EN 55024 (CISPR24)
- CENELEC EN 61000-3-2
- CENELEC EN 61000-3-3
- ETSI EN 301-893
- ETSI EN 300-328
- ETSI EN 300-440
- ETSI EN 301-489-1
- ETSI EN 301-489-7
- ETSI EN 301-489-17
- ETSI EN 301-489-24
- ETSI EN 301-511
- ETSI EN 301-908
- FCC Part 15 Subpart B Class B
- FCC Part 15 Subpart C (2.4 GHz)
- FCC Part 15 Subpart E (5 GHz)
- FCC Part 22 H (1xRTT/EVDO-0/EVDO-A)
- FCC Part 24 E (1xRTT/EVDO-0/EVDO-A)
- FCC Part 27 (WCS)
- R&TTE (89/336/EEC) & R&TTE (99/5/EC)

* Ask your representative for more information

** Compatible with Verizon 4G LTE networks where available. Standard 4G LTE and AWS spectrums supported.


¹ Weight represents approximate system weight measured with a 40Whr battery. Actual system weight may vary depending on component and manufacturing variability.

² Battery life varies by configuration, applications in use, utilized features and operating conditions.

³ Maximum battery capacity decreases with time and use. Xplore battery life estimates based on MobileMark® 2012 performance testing.

³ Approximate charging time. Validated charging from 5% to 90% with system on or system off.

© 2016 Xplore. All rights reserved. All product information is subject to change without notice. Xplore, Xplore Technologies, Motion Computing, Motion, are registered trademarks of Xplore in the United States and/or other countries. Microsoft Windows, Windows 7, Windows 8 and Windows 10 are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. Intel, the Intel logo, Atom, Intel Core and Core Inside are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries. BLUETOOTH is a registered trademark owned by Bluetooth SIG, Inc., U.S.A. and licensed to Xplore. All other trademarks and registered trademarks are the property of their respective owners.



The Intel® Core™ vPro™ processor is designed to strengthen security across the enterprise.